

Wi-Fi 4 Wireless Outdoor Access Point

WI-AP310-Lite

Overview

WI-AP310-Lite is a high-performance outdoor AP product that supports a 2.4GHz frequency band and uses 802.11 b/g/n technology. The wireless processing speed can reach up to 300Mbps. It comes with multiple power supplies, 24V PoE power supply, and 12V DC local power supply. It adopts an outdoor IP65 windproof, rainproof, dustproof, and sun protection grade shell design, so it can easily adapt to various harsh outdoor environments. It is widely used in outdoor cafes, home backyards, outdoor swimming pools, parks, and school playground scenes.

Features

Ideal for Outdoor Environment

WI-AP310-Lite IP65 weatherproof enclosure, outdoor Wi-Fi applications.

Multiple Power Supply Methods

Supports Passive 24V PoE and 12V DC local power, you can use Ethernet cables to transfer both electrical power and network data, making deployment more flexible and removing the need to install additional power cabling.

Multi-SSID

Support QVLAN binding multi-SSID, bind different SSIDs to different TAG VLANs, set different SSIDs for different departments of the enterprise, realize the isolation between SSIDs, and flexibly control the access rights of wireless networks.

Fast Roaming

802.11kvr fast roaming provides fast switching to the access point with the optimal signal when moving between APs.

Cloud Management

Users can conduct the comprehensive remote operation, management, and maintenance of the entire network equipment through the Wi-Tek cloud platform, and can also share the network with others for network hosting and collaborative management, to operate and maintain the enterprise network more efficiently.

Dual LAN Ports Design

The device adopts the dual LAN ports design. Even for complex networking requirements, it can easily and quickly support the expansion of third-party devices, such as cameras, network devices, etc.

Support Fit AP and Fat AP Mode

The device supports both Fit AP and Fat AP mode. A wireless network can be formed with multiple APs, or it can be used as a wireless router when deployed independently. The device offers more flexible configurations, more abundant application features, and more extensive applicable scenarios.

Mesh Technology

Mesh technology enables wireless connectivity between access points for an extended range, making wireless deployments more flexible and convenient.



Datasheet =



Specifications

| Products | WI-AP310-Lite |
|---------------------------------|--|
| Hardware Specifications | |
| | |
| Wireless Standards | 802.11n/b/g/a |
| Operating Bands | 2.4GHz |
| Antenna | 2.4GHz: 5dBi |
| Spatial Streams | 2.4GHz: 2x2 MIMO |
| Signal Rate | Up to 300 Mbps at 2.4GHz |
| Receiver Sensitivity | 2.4GHz: 802.11n:-69dBm@MCS7 -88dBm@MCS0. 802.11g:-73dBm@54Mbps -90dBm@6Mbps. 802.11b:-85dBm@11Mbps -94dBm@1Mbps. |
| Maximum Transmit Power | <23dBm |
| Interface | (2)10/100 Base-T Ethernet ports |
| Power Supply | DC 12V/1A (Not Included) 24V Passive PoE |
| Power Consumption | <10W |
| Installation | Pole/Wall mounting |
| External buttons | reset button (long press for 8 seconds to restore the factory default configuration) |
| Dimensions | 340mm * 85mm * 35mm |
| Environment | Operating Temperature: -40°C~55°C Storage Temperature: -40°C~70°C Operating Humidity: 5%~95% (non-condensing) Storage Humidity: 5%~95% (non-condensing) |
| Software Features | |
| Operating Mode | Fit AP, Fat AP |
| Wireless Function | Up to 8 SSIDs |
| | Support SSID hiding, enable/disable the wireless radio |
| | Manual and automatic channel assignment |
| | Manual and automatic bandwidth assignment |
| | TxPower control |
| | One-click mesh |
| Roaming | Support Layer 2 roaming |
| Wireless Security | Captive portal authentication Static blacklist and whitelist Wireless isolation between clients SSID to VLAN mapping Support 802.1X WPA/WPA2/PSK/WPA/WPA2-Enterprise |
| Internet Connection Type | Support Static IP, DHCP, PPPoE Dial-Up |
| Management | Support local management with web Support centralized management with AC Support remote management with the Wi-Tek cloud platform |
| Platform Management Features | Automatic RF adjustment via the platform Unified configuration via the platform Unified monitoring via the platform |



Wireless-Tek Technology Limited

Address: Room 402 4F, BiaoFan Technology Building, Bao'An

Avenue, FuYong Town, Bao'An district, ShenZhen


Website:www.wireless-tek.com

Tel:86-0755-32811290

Email:sales@wireless-tek.com

Technical Support:tech@wireless-tek.com







Cloud Management



Company Website

©2022 Wireless-tek Technology Limited. All Rights Reserved.

Version, V1.0, updated 2022.3.25.

The information in this document is subject to change without notice.

Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.