



MVP30-350 V2 Underway Profiler



Data Quality



Employee Safety



Efficiency



Real-Time



Vertical Profiling

The Moving Vessel Profiler (MVP), with over 25 years of expertise and thousands of successful surveys, is the undisputed market leader in automated, underway profiling systems. One of two smaller models, the MVP30-350 V2 is a compact yet powerful solution featuring an effective cable length of 350 meters. Supporting up to 6 independent data collection parameters and reaching 121 meters at 8 knots, the MVP30-350 V2 delivers precise, real-time results while maintaining a small physical footprint.

On Time or We Compensate

for SVPs & CTDs

Try Before You Buy

for Multiparameter Sondes

Love It or Leave It

for Moving Vessel Profilers



Promises Kept





Free-Fall Tow Body

Collect full water column data continuously in real time while your vessel is underway. Unlike other systems, the AML MVP provides a vertical profile. The sawtooth pattern above is a visual depiction of underway profiles collecting data in real time.

Real-Time High-Density Data Output

Possible parameters include:

- Sound Velocity
- Conductivity
- Temperature
- Depth/Pressure
- Phyco cyanin
- Rhodamine
- Tryptophan
- Dissolved Oxygen
- Chlorophyll A
- Turbidity
- Crude Oil
- CDOM/FDOM

Other sensors as well as multiple configurations are available. Please contact us for more options.



Key Benefits

- **Improved Data Quality** - Frequent and consistent data collection by the MVP ensures high-resolution, reliable results and improves credibility of survey outcomes.
- **Increased Crew Safety** - By automating the collection of water column data, the MVP minimizes the need for manual deployment and retrieval of sensors, keeping crew members safe from exposure to harsh weather or hazardous conditions.
- **Increased Efficiency** - The MVP collects water column data seamlessly while the vessel is underway, eliminating the need to stop for profiling, in turn reducing survey time and operational costs.
- **Real-Time Profiling** - The MVP provides immediate access to collected data, enabling prompt analysis and informed decision-making during survey operations.
- **Vertical Profiling** - The MVP collects reliable data across a wide range of depths, allowing customers to gain a complete understanding of the water column.

Performance Specifications

Vessel Speed	Depth Obtained in Meters			
	MVP30 V2	MVP30-350 V2	MVP200	MVP300
0 knots	125m	350m	600m	3400m
2 knots	90m	245m	457m	2200m
4 knots	73m	200m	368m	1650m
6 knots	60m	155m	310m	1250m
8 knots	51m	121m	265m	740m
10 knots	42m	70m	235m	460m
12 knots	30m	30m	200m	300m

