

# Tractor 3 Pt. Lay-Flat Retrieval Machine



**LF0801-001**

## **3-PT Front/Rear Lay-Flat Layer Retriever**

The Tractor 3 Pt. Lay-Flat Machines allow users the ability to layout and collect pliable irrigation piping systems (Lay-Flat), safely and efficiently, this tractor powered version is the simple solution for handling reusable rolls of sub-main manifolds from water delivery systems.

Built Andros tough, this high quality engineered device provides growers the flexibility and insurance to overcome nearly all obstacles with placement and re-spooling.

Built with an articulating spooling head, slide slopes and ditches are a breeze when the user can orientate spool to match ground level.



**MR1303-001**

## **Triple Head Lay-Flat Machine**

### **GENERAL FEATURES**

- 4 to 1 ratio controller for easy re-spooling.
- Adjustable operator Station.
- Adjustable Spool Driver for 4", 6" and 8" Lay-Flat.
- Variable Speed Controller for Speed Adjustment.
- Bolt on Cat II Adapter.
- Front or Rear Mount Capable.
- Shade Umbrella.

### **OPERATIONAL FEATURES**

- No lifting required.
- Machine hydraulically loads and unloads full reels and can handle 4", 6", & 8" lay-flat.
- Safe and Simple to operate.
- No lifting means operators are protected from injuries caused by lifting rolls of lay-flat that can weigh upwards of 300 pounds.
- This machine is equipped with multiple safety features to protect the operator during mobile and stationary operation.
- All retrieval controls are clearly marked and accessible during both mobile and stationary operation.