

Raises the bar for standard set infusion pump technology

- Flow Check Occlusion Alarm-an in-line resistance display of incremental back pressure
- Flow Rate Calculation is automatic after volume and time are selected
- Slide Clamp Option offers an additional step to protect against inadvertent gravity-free flow
- Front Panel Lock-out protects against tampering
- Programmed Delivery Profile allows up to 10 steps, individualizing control of infusion ramping and tapering
- Incremental Flow Rate can deliver 1-99.9 mL/hr in increments of 0.1 mL/hr
- Automatic Restart once occlusion clears
- Automatic Piggybacking of secondary medications



► Specifications

- Size (H x W x D): 29 cm x 20 cm x 13 cm (11.4" x 8" x 5.1")
- Weight: 5.3kg (11.6 lb)
- Channels: Single
- Range of Flow Rate: 1-99.9 mL/hr in 0.1 mL/hr increments and 1-1,999 ml/hr in 1 mL/hr increments
- Maximum VTBI: 1-9,999 mL
- Automatic Restarts: 09
- Alarm Intervals: 1-7 seconds
- Battery/Time: 12 volt, 2.0 ampere, sealed lead acid battery
Recharge: 80% charged within 8 hr. battery life; 6 hr at 1,400 mL/hr