# **Baxter AS50**

### Syringe Pump

## Delivers precise, controlled infusions

Developed to meet the infusion needs in NICU, Anesthesia and Critical Care, the Auto Syringe AS50 Infusion Pump delivers precise, controlled infusions.

#### **FEATURES**

- > Configurable Drug Library
- > Syringe Plunger Detection
- > Backlight Display
- Adjustable Occlusion Specialty
- Selectable Modes of Delivery
- > Accepts Syringe Sizes from 1-60cc

- Battery Voltage Indicator
- > Adjustable "Near End" Alert
- > RS232 Communication Port
- Syringe Types: Monoject, use all B-D, Terumo. 1ml-60ml on all three.





### **SPECIFICATIONS**



Weight: 3.2 lbs.



Dimensions: 3.4" x 2.6" x 10"



Flow Rate Accuracy: ± 3% of full scale plunger travel (not including syringe tolerance)

Volume Accuracy: ± 3%, or .007" of travel, whichever is greater (not including syringe tolerance)

**Syringes:**B-D: 1, 3, 5, 10, 20, 30, 60 mL
Terumo: 1, 3, 5,10, 20, 30, 60 mL

Flow Rate Range: .01 mL/hr to 438 mL/hr, depending on the syringe

Delivery Volume: Full syringe volume for 1-60 mL syringes

Data Display: Self-prompting, multi-field

> Status Display: Nine-LED array

Power Requirements:
AC: 105-125V 60Hz
(battery charger)
DC: internal rechargeable battery
pack

Battery Operating Time: 5 hrs at 100 mL/hr, 12 hrs at 2 mL/hr using a 60 mL syringe, following a charge of no less than 16 hours

2625-2022-06-20

