

Tuttnauer 3870EA

Automatic Autoclave

Features a closed-door active drying system to maintain sterility

FEATURES

- New contemporary design with an easier to read bright blue display panel.
- Pre-loaded cycles for: unwrapped instruments; wrapped/packs; liquid and additional drying cycle.
- Cycle time is (hot) 40 minutes, (cold) 55 minutes.
- The Chamber is 15" x 30" with a 22 gallon volume (85L), and holds 15 full standard cassettes.
- All program parameters can be changed and stored.
- Automatic shut off at the end of both the sterilization and dry cycles.
- Audible and visual cycle interruption alert.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Low water sensor prevents activation of sterilization cycle when there is insufficient water in the chamber or reservoir.
- Constant monitoring of temperature and pressure for sterilization. Power outage recovery system.
- Door design prevents steam from coming in contact with control panel.
- Optional printer.
- High Efficiency air pump.
- Decreased overall drying time.
- Closed door drying.
- Hepa filter 0.2µm air filter (replaceable)
- Circulates hot air after the sterilization cycle for fast drying.



SPECIFICATIONS



Shipping Weight:
213 lbs (97 kg)



Chamber Dimensions:
15" x 30" (384 mm x 760 mm)

Overall Dimensions:
26" W x 34.5" D x 20.6" H
(665 mm x 875 mm x 525 mm)

Tray Dimensions:
11.3" W x 26.6" D x 1" H
(286 mm x 675 mm x 25 mm)
13.8" W x 26.6" D x 1" H
(350 mm x 675 mm x 25 mm)



Volume:
22 gallons | 85 Liters

Standard Cassettes: 15 full

Number of Trays: 2

Cold Cycle Time:
32 minutes

Hot Cycle Time:
23 minutes



Voltage: 230V

Frequency: 50/60 Hz

Power: 3000W

Current: 13.6A

1306-2022-10-11