



INSTALLATION Nordic Flooring Marine

INSTALLATION

Manufacturer's instructions must be followed. The floor can be installed on subfloors, 1mm steel or a higher thickness metallic surface that has been suitably prepared. Existing resilient floors must be removed and the subfloor re-prepared. The floor must not be installed externally/outdoors or in unheated locations.

It is preferable to protect the floor from heavy traffic for 24 hours after installation. The floor must not be washed for 48 hours.

SUBFLOOR

It is the responsibility of the installing contractor to ensure the subfloor is fit to receive a resilient floor. To ensure good quality appearance and adhesion, the floor or subfloor must be hard, smooth, clean, dry and free from defects.

PREPARATION

Preparation includes using a suitable degreaser. The floor surface should be abraded and any surface rust removed. Ensure the floor is clean before proceeding with the installation. Use a suitable levelling compound to ensure that no irregularities show through to the surface of the finished floor.

The tiles, adhesive and floor or subfloor should be allowed to stabilise to constant temperature conditions of 18-27 °C (64-81 °F) for a period of 24 hours before, during and after installation. Tiles must be stored flat.

ADHESIVE RECOMMENDATIONS

Select the appropriate adhesive for installation, ensuring that the adhesive has been protected from frost during storage. Ask your adhesive supplier for recommendation. Only Marine certified adhesives should be used. Use the recommended trowel notch size and do not use worn trowels. Roll the floor with a 45kgs (100lbs) roller before the adhesive has completely set to ensure a good bond between tile, adhesive and floor.

Do not walk on freshly installed tile. Follow the adhesive supplier recommendations. Clean away excess adhesive with a damp cloth (lukewarm water) before it is allowed to dry. It is imperative that the correct adhesive is used.

Please contact us or visit our homepage for further information: www.nordicflooringmarine.se