


TECHNICAL SPECIFICATION Nordic Flooring Marine

Type of flooring	EN 649	Heterogenous PVC design floor PU coated
Size Wood	EN 427	152,4 x 914,4 mm
Size *Wood Special order, min 150 m ²	EN 427	101,6 x 914,4 mm 177,8 x 1219,2 mm 228,6 x 1219,2 mm
Size Stone, Liene, Futura	EN 427	457 x 457 mm
Size Concrete	EN 427	305 x 610 mm
Size Plain	EN 427	305 x 305 mm
Size Stripes	EN 427	5 x 914,4 mm
Thickness overall	EN 428	2,5 mm (stripes 2,0 mm)
Thickness wear layer	EN 429	0,5 mm + PUR/PU Coating
Weight in total	EN 430	4,2 kg/m ²
Surface Wood		Deep Emboss
Installation of material		See installation instructions
Maintenance		See maintenance instructions
Wear group classification	EN 685	33, 42
Chemical resistance	EN 423	Pass
Castor chair resistance	EN 425	Pass
Residual indentation	EN 433	0,05 mm or less
Dimensional stability	EN 434	Pass
Flexibility	EN 435	Pass
Abrasion resistance	EN 660	Group T
Slip resistance	DIN 51130	R 9
Sound reduction	DIN 52210	4 dB
Light stability	ISO 2105 B02	> 6
Floor heating		Suitable, max +27 °C
IMO Resolution	MSC61 (67) Part 2 MSC61 (67) Part 5	Pass Pass



Notified Body No.
0575



EN 14041

April 2016