
# **GALLIUM PRO**







# **GALLIUM PRO**



#### **GEOMETRY**

SIZE CLASSIC		XXS* 44-46	XS* 47-50	S* 51-53	M* 54-56	L* 57-59	XL* 60-62
Α	cm	41.5	45.5	49	53	56.5	59.5
В	deg	75.5	74.5	74	73.5	73	72.5
С	deg	71	72	72.7	72.7	72.7	73
D	cm	50.2	52	54	56	57.5	59.5
E	cm	40.6	40.6	40.6	40.8	41	41
F	cm	96	96	97	98	100	101.5
G	cm	7.5	7.5	7.5	7.5	7.5	7.5
H1	cm	7.7	8.2	10.9	13.9	16.2	18.9
H2	cm	9.1	9.6	12.3	15.3	17.6	20.3
H3	cm	10.1	10.6	13.3	16.3	18.6	21.3
ī	cm	66	69	73	77	79	81.5

<sup>\*</sup> Sloping Top Tube



# **POSITIONING VERSATILITY**

FOR TACKLING THE TALLEST MOUNTAINS OR SIMPLY ENJOYING SUPERIOR DOWNHILL STABILITY AND HANDLING



## **UCI APPROVED**

FRAME AND FORK ARE APPROVED BY THE UNION CYCLISTE INTERNATIONALE



# **SIZE-SPECIFIC GEOMETRY**

WELL BALANCED ERGONOMIC FIT FOR EVERY FRAME IN EVERY SIZE



### **OPTIMAL BALANCE**

WINNING COMBINATION OF POWER, LIGHTNESS AND RIGIDITY FOR RIDERS OF ALL SHAPES AND SIZES



EVERY FRAME SIZE HAS THREE HEAD TUBE HEIGHTS FOR INCREASED RIGIDITY; SYSTEM PRESERVES 5% AND 11% MORE INCREMENTAL FRONTAL RIGIDITY VS. STANDARD SPACERS WHEN THE HANDLEBAR IS SET AT 15MM AND 25MM, RESPECTIVELY











