

GF 85

HIGH PERFORMANCE DEGREASING SOLVENT

VERSION 1 - JANV.-17

WWW.MECATECH-PERFORMANCES.COM

DEFINITION

- Universal technical liquid for all difficult cleaning and degreasing operations
- Replaces chlorinated solvents.
- Very high solvent power.
- Evaporates in less than 30 minutes

APPLICATIONS

- Cleaning of heavily polluted metal parts
- Preparation of surfaces before gluing or painting.
- Cleaning of non-crosslinked adhesives or sealants (eg cyanoacrylates)
- Precision degreasing, defluxing

FICHE TECHNIQUE

HOW TO USE

- GF 85 must be used pure, cold.
- GF 85 can be used in a fountain, in a tank (by immersion of the parts to be degreased), in an ultrasonic bath, but also simply with a rag or brush.

CARACTERICS

| | |
|---|--------------|
| • Appearance | Clear liquid |
| • Odour rating | 3 |
| • Density at 20 °C (Kg/m3) | 823 |
| • Viscosity at 40° C (mm ² /s) | 1.01 |
| • Flash point / closed vessel (°C) | 28.5 |

PACKAGING

- Packaging: Can of 5 litres, Metal barrel of 30 litres
- Article number: 885005 - 885030