

WS 40 - 5 W 40

High performance engine synthetic oil
Anti-wear and anti-friction « WS » nanotechnology

VERSION 2 - SEPTEMBRE 2012

WWW.MECATECH-PERFORMANCES.COM

DEFINITION

- New generation engine oil complying with the higher standards and manufacturer approvals.
- Nanotechnology of « WS » lubrication, exclusive of MECATECH, giving an extraordinary protection and lubrication.

PROPERTIES

- Suitable and adapted for the lubrication of petrol engines or diesel engines with or without DPF.
- Allows a very good cold start, reduces emissions and fuel consumption.
- Significantly reduces the losses of viscosity in use and the problems caused by shear phenomena.
- Protects against wear, reduces oil consumption, extends the time between oil changes.

PERFORMANCES

- Approved ENI I-SINT 5W40 formula :
- ACEA C3,A3/B4-04
- API SM/CF
- BMW Longlife 01
- MB 229.3 and MB 223.2
- RN0700-11-07 and RN 0710-11-06

TECHNICAL DATA

- VW 502 00 + 505 00
- PORSCHE A40

CHARACTERISTICS

SAE GRADE

5W/40

- Viscosity at 100° C mm²/s 13.1
- Viscosity at 40° C mm²/s 76
- Viscosity at -30° C mPa.s 6200
- Viscosity index 174
- Flash point V.O. °C 230
- Pour point °C -36
- Density at 15° C kg/l 0.854

PACKAGING

- 1 and 5 litres cans.
- 30 and 200 litres barrels
- REF : 206xxx



The content of this technical sheet is aimed at giving you advices. It does not imply any commitment on our part.