

# SILICONE FLUIDE

CLEAN LUBE FLUID OF LOW VISCOSITY MÉTHYLPOLYSILOXANES  
/RELEASE AGENT

VERSION 1 – JANUARY 2020

[WWW.MECATECH-PERFORMANCES.COM](http://WWW.MECATECH-PERFORMANCES.COM)

## DEFINITION

- ◆ SILICONE FLUIDE is a combination of methylpolysiloxanes fluids formulated in fast drying solvents.
- ◆ SILICONE FLUIDE is a release agent for plastic and rubber molds.
- ◆ Allows also clean lubrication of seals, hinges, locks, guides, chains, mechanisms subjected to low loads, paper cutters...

## INTRODUCTION

- ◆ This product is clear, colourless, odourless after the solvents evaporate.
- ◆ Leaves no stain.
- ◆ Low viscosity silicone with antistatic effect. Dielectric agent.
- ◆ After the solvents evaporate, the product might have incidental contact with food (components complying with the 1992 CNERNA guide, and silicone complying with the FDA 21 CFR 178.3570 part).
- ◆ The 360° valve allows the use in all positions.

## OPERATING INSTRUCTIONS

- ◆ Shake well before use.
- ◆ Molds and all surfaces to be treated have to be first degreased with usual solvents.
- ◆ Spray on the surfaces, wait for 2-3 minutes and repeat if necessary.



## PHYSICOCHEMICAL CHARACTERISTICS

- ◆ Aspect Clear
- ◆ Colour Colourless
- ◆ Odour Light
- ◆ Density at 15°C NFT 60101 690 kg/m<sup>3</sup>
- ◆ Flash point VC ASTMD 56 <0°C

## SAFETY DATA

- ◆ Consult the SDS of the products available on our website [www.mecatech-performances.com](http://www.mecatech-performances.com). Professional use.

## PACKAGING

- ◆ Packaging : 650 / 400 ml spray can
- ◆ Reference : 450012

*The content of this technical sheet is aimed at giving you advices.  
It does not imply any commitment on our part.*