

# WS 30 - 5 W 30

High performance synthetic engine oil Anti-wear, anti-friction « WS » nanotechnology

#### WWW.MECATECH-PERFORMANCES.COM

JE MAINTENAI

PERFORMANCES

SOCIÉTÉ D'EXPLOITATION DES LUBRIFIANTS DAGANAUD

## DEFINITION

- New generation engine oil complying with the higher standards and manufacturer approvals.
- Nanotechnology of « WS » lubrication, exclusive of MECATECH, giving an extraordinary protection and lubrication.

#### PROPRERTIES

- Suitable and adapted for the lubrication of petrol engines or diesel engines with or without DPF.
- Allows a very good cold start.
- Protects against wear, reduces oil consumption, extends the time between oil changes.

## PERFORMANCES

- Approved ENI I-SINT 5W30 formula :
- ACEA A3/B4-04
- ACEA C3 (performance)
- BMW Longlife 04
- MB 229.51 and MB 223.2
- VW 504 00 + 507 00
- PORSCHE C30



## CHARACTERISTICS

#### SAE GRADE

#### 5W/30

•	Viscosity at 100° C	mm²/s	12
•	Viscosity at 40° C	mm²/s	74
•	Viscosity at -30° C	mPa.s	6100
•	Viscosity index		161
•	Flash point V.O.	°C	210
•	Pour point °C		-42
•	Density at 15° C	kg/l	0.850

## PACKAGING

- 1 and 5 litres cans.
- 30 and 200 litres barrels.
- REF : 204xxx

The content of this technical sheet is aimed at giving you advices. It does not imply any commitment on our part.



DNV-GL