

MécaTech

ORTIFIANT HUILE

NON DE SYSTER

ISO 9001

OIL PROTECTOR Oil protection – Transmissions & Engines

VERSION 1 - AUGUST 2017

WWW.MECATECH-PERFORMANCES.COM

JIT DE MAINTENANC

ES PERFORMANCES

SOCIÉTÉ D'EXPLOITATION DES LUBRIFIANTS DAGANAUD

DEFINITION

- Maintains optimum viscosity.
- Reduces the risk of degradation and oxidation (friction, rubbing, temperature)
- Improves the flow properties of oil and prolongs its life
- Prevents lacquer and resin deposits in parts such as hydraulic systems, valve bodies in automatic gearboxes, tappets, camshaft timing and valve lift adjustments in engines.

ADVANTAGES

- Maintains the properties of oil over a longer period.
- Keeps piston rings (grooves) and internal parts clean.
- Reduces build-up and deposits of sludge.

HOW TO USE

- A 300 ml dose treats 4 to 6 litres of engine oil and 6 to 10 litres or gearbox oil
- Pour the dose into the oil.
- Recommended treatment for every oil change.

COMPATIBILITY

- Compatible with all types of gearboxes, automatic, robotised and manual, and all types of mineral, semi-synthetic and synthetic fluids.
- Compatible with all types of petrol and diesel engines, and all types of mineral, semi-synthetic and synthetic oils
- Safe for after-treatment systems of exhaust gases: catalyst, DPF etc. ...

PACKAGING

Packaging:

Article number:

Dose of 300ml MT027

The information contained in this data sheet is intended to advise you. They do not imply any commitment on our part.

SELD / MecaTech • 6 rue Jules GUESDE - 69360 Saint Symphorien D'Ozon - FRANCE - Fax: 04 78 21 80 70