

## A<sub>2</sub>B<sub>2</sub>

### ASPHALT ANTI-STICKING BIODEGRADABLE BIODEGRADABLE, EMULSIFIABLE, WITHOUT VOCs

VERSION 1 - OCTOBRE 2012

[www.mecotech-performances.com](http://www.mecotech-performances.com)

#### PROPERTIES

- ◆ A<sub>2</sub>B<sub>2</sub> protects all surfaces (metallic, plastic, glass...) from the sticking of tar, bitumen and resins.
- ◆ A<sub>2</sub>B<sub>2</sub> is effective for many hours on hot or cold surfaces.
- ◆ A<sub>2</sub>B<sub>2</sub> is 98% biodegradable in 28 days.
- ◆ Formulated from compounds of vegetable origin.

#### HOW TO USE

- ◆ A<sub>2</sub>B<sub>2</sub> protects dump trucks and finisher, conveyor belts, cylinders, compactors wheels, hand tools...
- ◆ A<sub>2</sub>B<sub>2</sub> must be diluted in water (20 to 30% dilution).
- ◆ Sprays on the surfaces to be treated.
- ◆ Leave to dry before contact.

#### PACKAGING

- ◆ CAUTION : protect from frost
- ◆ Cans of 5 liters and barrels of 30 and 200 liters.
- ◆ Reference: 830005 - 830030 - 830200

*The information in this technical leaflet are given as advice and don't imply any commitment on our part.*

