

KIT KB5001

**BIOCIDAL AND COMPLETE DIESEL TREATMENT FOR
STATIC TANKS UNTIL 5000L**

WWW.MECATECH-PERFORMANCES.COM

VERSION 1 - FEBRUARY 2019

INTRODUCTION

Kit which contains TFB -broad range biocide for intermediate hydrocarbons- and TC1 -complete treatment for diesel with optimal cleaning effect.

Most of the effects of the TFB biocide are observed after 6 hours. However, 36 hours are necessary to get a complete efficiency.

OPERATING INSTRUCTIONS

- If necessary, drain the tank bottom which contains water and sludge and dispose of it considering the current legislation.
- Pour the TFB into the tank before filling it up to ensure TFB is properly dispersed.
- The treatment is recommended every 6 to 12 months according to our fuel quality practice - DQC MECATECH.

PACKAGING

A 1L- bottle of TFB (186001) + a 5L-bottle of TC1 (131005) for storage tanks from 2500L to 5000L.

HOW TO DISPOSE OF THE EFFLUENTS

- After curative treatment with TFB and before disposal, effluents and water bottoms have to be diluted. Indeed, such as most of biocides, TFB reveals to be harmful to aquatic life.

- Dilution after treatment: since TFB is a biodegradable biocide, its degradation occurs after its dilution below effect level. The bigger the dilution the faster the degradation
- Deactivation of non-used undiluted TFB: Add four volumes of slightly acid solution of sodium metabisulphite (NaS_2O_5) or sodium bisulphite (NaHSO_3), for one volume of TFB.
- Do not dispose of TFB in sewers.

The content of this technical sheet is aimed at giving you advices. It does not imply any commitment on our part.

