

MoS2 - PL

ANTI WEAR TREATMENT GEAR BOX / PS / AXELS

VERSION 1 - JANUARY 2020

WWW.MECATECH-PERFORMANCES.COM

TECHNICAL DATA

DEFINITION

- ◆ Colloidal molybdenum disulphide anti-wear treatment.
- ◆ Reduces noises and lowers frictions while forming a high resistance lubricating film on all sliding surfaces.
- ◆ Reduces wear and stops the phenomena of gears wear. Facilitates gear shifting.
- ◆ Recommended in case of strong wear, running noises, and harsh use.

OPERATING INSTRUCTIONS

- ◆ Dosage from 3 to 5 % :
A 1L-bottle for 20 or 30 litres of oil.
- ◆ Shake well before use, then introduce the dose needed in the crankcase using a clean syringe.
- ◆ Recommended for transmissions, transfer boxes and differentials.
- ◆ Not for use in automatic transmissions and limited slip differentials.
- ◆ Compatible with all kinds of mineral or synthetic oils.
- ◆ Recommended in addition to GDA® evolution Ref. 101 in case of noisy top gears or axels.

PHYSICOCHEMICAL CHARACTERISTICS

- | | |
|--------------------------|----------------|
| ◆ Colour | amber |
| ◆ Odour | characteristic |
| ◆ Density at 20°C | 0.955 |

SAFETY DATA

- ◆ Consult the SDS of the products available on our website www.mecattech-performances.com.

PACKAGING

- ◆ Packaging : 1L-dose treats 20 to 30 liters
- ◆ Reference : MT522

The content of this technical sheet is aimed at giving you advices. It does not imply any commitment on our part.

