

## User Instruction Sheet

Select the suitable glove size using the label. Before usage, inspect the gloves for any defects. If the gloves are defective, dispose them immediately. If in doubt do not use the gloves, get a new pair of gloves.

### EN 420:2003+A1:2009

- Name and full address of manufacturer or his authorized representative.  
Advansafety, Biyagama Export Processing Zone – A, Walgama, Malwana, Sri Lanka
- Name & address of the notified body responsible for both EU Type Examination and on-going conformity:  
SATRA Technology Europe Ltd., Bracetown Business Park, Clonee, Dublin 15, D15 YN2P, Ireland, NB No.: 2777
- Glove designation (name or reference):  
220-15SD - Nitrile, Flock Lined 15mil (0.38mm) Work Glove
- Information on the available size range Full Dipped Sizes: Small, Medium, Large, Ex-Large, 2XL,3XL
- Reference to the relevant specific European standards  
EN 388:2016  
EN 420:2003+A1:2009  
EN ISO 374-1:2016  
EN374-2:2014  
EN16523-1:2015  
EN 374-4:2013
- Certified performance level of the product as follows. Product is considered to be Category III of PPE hand protection and certified in accordance with PPE regulation (EU) 2016/425

*Pictogram followed by the performance levels.*



Certified performance level of the product as follows. Product is considered to be Category III of PPE hand protection and certified in accordance with PPE regulation (EU) 2016/425

Standard	Claus/Property	Results
EN 388:2016	6.1 Abrasion resistance	level 4
	6.2 Coupe Test: Blade cut resistance	level 1
	6.3 TDM:Cut Resistance Method EN ISO 13997:1999	X
	6.4 Tear resistance	level 0
	6.5 Puncture resistance	level 2
EN420:2003+A1:2009	5.1 Length & Fit	Pass
	5.2 Dexterity	Level 5
	AZO Dyes	Pass
	pH Value	Pass

Special Note: X-mean material not considered to be suitable for this test.

## User Instruction Sheet

EN 374-1:2016

Method	Chemical Name	Performance level
EN 16523-1:2015	Methanol 67-56-1	2
EN 16523-1:2015	Acetone 67-64-1	0
EN 16523-1:2015	n-Heptane 142-85-5	6
EN 16523-1:2015	Sodium hydroxide 40% 1310-73-2	6
EN 16523-1:2015	Sulphuric acid 96% 7664-93-9	3
EN 16523-1:2015	Nitric acid 65% 7697-37-2	3
EN 16523-1:2015	Acetic acid 50% 64-19-7	3
EN 16523-1:2015	Ammonia hydroxide 25% 1336-21-6	5

7. Basic explanation: The end user needs to know what the levels means under the pictogram.
8. Product does not contain any known substances that may cause harm to the wearer's health and there is no possible allegiance.
9. Washing & cleaning instructions: Wipe clean only
10. Declaration of conformity can be viewed by visiting this link. <http://www.advansafety.online>
11. Warning:
  - a. Gloves not be worn when there is a risk of entanglement by moving parts of machines and the glove must not come in contact with a naked flame.
  - b. This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals
  - c. The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400mm-where the cuff is tested also) and relates only to the chemical tested. It can be different if the chemical is used in a mixture.
  - d. It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from the type test depending on temperature, abrasion and degradation.
  - e. When used, protective gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, snagging, rubbing, degradation caused by the chemical contact may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves.
  - f. Before usage, inspect the gloves for any defect or imperfections.
12. Cleaning & maintenance:

The gloves should be stored in the original packing at a dry and clean place. Please avoid exposing the glove to high temperature, humidity or direct sunlight light.
13. Shelf life of product:

Recommended shelf life of product is 5 years under controlled environment condition, product should store away from direct sunlight & away from humidity. Temperature of warehouse should not exceed more than 35 degree Celsius, product should store under proper packaging.

## User Instruction Sheet

### Requirements for EN 388:2016 levels of performance

Levels of performance EN388:2016					
Test	Level 1	Level 2	Level 3	Level 4	Level 5
Abrasion resistance (number of rubs)	100	500	2000	8000	–
Coupe test Blade cut resistance (index)	1.2	2.5	5	10	20
Tear resistance (N)	10	25	50	75	–
Puncture resistance (N)	20	60	100	150	–

### Levels of performance EN ISO 13997:1999

Test	Level A	Level B	Level C	Level D	Level E	Level F
TDM:cut resistance	2	5	10	15	22	30

### Requirements for EN 374 - 1:2016 levels of performance

#### Levels of performance EN 374 - 1:2016

Level	Measured breakthrough time (minutes)
1	>10
2	>30
3	>60
4	>120
5	>240
6	>480

Manu. Date      Xx/xx/xxxx  
Exp. Date        Xx/xx/xxxx