

AT-PRO5-101-RX
Specification Sheet
PRO5 4K Fiber/Copper Receiver

Description

The Atlona AT-PRO5-101-RX is an AV extension receiver featuring SDVoE® 10GbE connectivity for receiving ultra-high definition video and audio from the AT-PRO5-MX810 matrix switcher. Part of the PRO5 Series, the PRO5-101-RX is HDCP 2.3 compliant, and supports 4K/60 4:4:4 and HDR at HDMI® data rates up to 18 Gbps. It features an RJ45 port, and an SFP+ cage for copper or fiber optic connectivity to receive video, embedded audio, Gigabit Ethernet, and RS-232 and IR control signals from the matrix switcher. The RJ45 port allows extension up to 330 feet (100 meters) over CAT6a UTP cable, along with PoE for powering the PRO5-101-RX, while the SFP+ cage can be used with a compatible fiber optic module to extend from 38 meters up to 10 kilometers over fiber optic cable. The PRO5-101-RX SDVoE receiver, together with the PRO5-MX810 HDMI to SDVoE matrix switcher, is ideal for a wide range of commercial applications requiring multi-zone AV distribution with long-distance signal extension.

Applications

Multi-zone AV distribution

- A PRO5 Series system, with the PRO5-MX810 and eight PRO5-101-RX receivers gives it ample capacity to serve displays in remote locations. This is applicable to a wide variety of environments such as lecture halls, active classrooms, large conference rooms, boardrooms, divisible rooms, retail, hospitality, and houses of worship.

AV signal extension

- The PRO5-101-RX offers standard 10 Gigabit Ethernet connectivity with a choice of CAT 6a UTP cabling, or the use of a compatible SFP+ module to extend signals over single mode or multi mode fiber. Fiber optic cabling can be an appealing option to cover very long distances, and whenever there is the availability of dark (unused) fiber in a facility's cable plant.

Key Features

SDVoE® receiver for video, audio, Gigabit Ethernet, and bidirectional IR and RS-232 control signals

- Receive AV, control, and Ethernet from the AT-PRO5-MX810 matrix switcher using SDVoE technology.
- Ideal for commercial applications requiring multi-zone AV distribution with long-distance signal extension.

High-performance, SDVoE-based, point-to-point AV extension

- Leverage 10GbE connectivity for ultra-high definition video and audio delivery between source and destination devices.
- Full-bandwidth distribution without the cost of a 10GbE network.

SDVoE extension input with copper or fiber optic connectivity (1)

- RJ45 port allows extension up to 330 feet (100 meters) over CAT6a UTP cable.
- SFP+ cage can be used with compatible fiber optic transceiver module (2) to extend from 38 meters up to 10 kilometers over fiber optic cable.
- System design and integration versatility for distributing signals over 10 Gigabit Ethernet copper or fiber optic cables.

4K/UHD capability @ 60 Hz with 4:4:4 chroma sampling, plus support for HDR formats

- Ideal for 4K/UHD and HDR-capable sources and displays.
- Compatible with HDR10, HDR10+, Dolby® Vision™, and HLG (Hybrid Log-Gamma).

HDCP 2.3 compliant

- Adheres to latest specification for High-bandwidth Digital Content Protection.
- Allows protected content stream to pass between authenticated devices.

Remotely powered by AT-PRO5-MX810 matrix switcher, or locally powered

- When receiving AV signals over the RJ45 port, industry standard IEEE 802.3af PoE is supplied by the PRO5-MX810. Also can be locally powered with optional Atlona AT-PS-48083-C power supply.
- Allows convenient receiver installation at a display or projector without the need for local AC power. (3)

Audio de-embedding

- De-embeds two channel LPCM audio to a balanced, analog output.

Multi-channel audio compliant

- Passes through multi-channel audio formats from the HDMI inputs.
- Supports PCM, Dolby® Digital, Dolby Digital Plus™, Dolby TrueHD, Dolby Atmos®, DTS® Digital Surround™, DTS-HD Master Audio™, and DTS:X®.

EDID management

- Manages EDID communications between source, switcher, and displays; allows integrators to force a source to transmit preferred video resolution and audio format.
- Ensures desired audio formats and video resolutions are provided to the AV system.

HDCP 2.3 management

- Automatically reports HDCP compliance status to the source based on the sink device. HDCP compliance can be disengaged through Velocity Device Manager, API, or the web GUI.
- Allows non-protected material from PCs to pass to non-compliant displays, streaming devices, and teleconference systems; protected content is not transmitted.

- Displays a green splash screen as visual confirmation that protected content is being blocked from transmission to a non-compliant display.

Intuitive GUI-based configuration using integrated web server (from the PRO5-MX810 matrix switcher)

- Offers menu-based configuration of network settings, EDID and HDCP management, audio settings, and more.
- Allows fast configuration of internal product settings and troubleshooting from a mobile device or PC in the field.

TCP/IP control

- Flexible control options for compatibility with the Atlona Velocity™ control system, as well as other third-party control systems.
- Receiver can be controlled and managed from the PRO5-MX810 matrix switcher, or locally (when Ethernet pass-through is disengaged).
- Reduces integration time and costs.

Easy to configure and manage with Velocity Device Manager

- Centralized, network-based configuration and management of Atlona IP-controllable products and systems.
- Receiver can be managed from the PRO5-MX810 matrix switcher, or locally (when Ethernet pass-through is disengaged).
- Manage configuration and firmware updates for AV devices spanning a facility, building, organization, or enterprise.
- Available as a part of Velocity control systems or as a free virtual machine software download.

Field-updatable firmware

- Device can be updated in the field via the web GUI or Velocity Device Manager from the PRO5-MX810.

Front panel power and signal status LEDs

- LED indicators provide power, device and video signal status, and SDVoE extension link status information.
- Provides local, convenient setup and troubleshooting when network access is not available.

Low-profile, 1.02 inch (26 mm) high enclosure

- Easy installation into confined spaces behind displays and above projectors.

Included accessories

- Surface mounting hardware and external universal power supply.

Specifications

Video	
Signal	Input: SDVoE (RJ45, SFP+) Output: HDMI
Copy Protection	HDCP 1.4 / 2.2 / 2.3
Pixel Clock	600 MHz
UHD / HD / SD	4096 × 2160 @ 60, 50, 30, 25, 24 Hz 3840 × 2160 @ 60, 50, 30, 25, 24 Hz 1920 × 1080p @ 60, 59.94, 50, 30, 29.97, 25, 24, 23.98 Hz 1920 × 1080i @ 30, 29.97, 25 Hz 1280 × 720p @ 60, 59.94, 50 Hz 720 × 576p @ 50 Hz; 720 × 576i @ 25 Hz 640 × 480p @ 60, 59.94 Hz; 640 × 480i @ 30 Hz
VESA	2560 × 1600, 2048 × 1536, 1920 × 1200, 1680 × 1050, 1600 × 1200, 1440 × 900, 1400 × 1050, 1366 × 768, 1360 × 768, 1280 × 1024, 1280 × 800, 1152 × 864, 1024 × 768, 800 × 600, 640 × 480
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit
HDR	HDR10, Hybrid-Log Gamma (HLG), and Dolby® Vision™ @ up to 60 Hz

Audio	
HDMI Pass-Through Formats	LPCM 2.0, LPCM 5.1, LPCM 7.1, Dolby® Digital, Dolby Digital Plus™, Dolby TrueHD, Dolby Atmos®, DTS® Digital Surround™, DTS-HD Master Audio™, DTS:X®
Bit Depth	Up to 24-bit
Sample Rate	32, 44.1, 48, 88.2, 96, 176.4, 192 kHz
Analog Audio Format	Stereo 2-channel
Analog Audio Type	Balanced

Ethernet	
Port	1 × RJ45
Speeds	10/100/1000 Mbps
Addressing	DHCP, Static, APIPA

RS-232	
Port	1 × 3-pin captive screw (TX, RX, GND)
Use	Pass-through from the AT-PRO5-MX810
Baud Rates	2400, 4800, 9600, 19200, 38400, 57600, 115200
Data Flow	Bidirectional

CEC	
Ports	1 × HDMI OUT, Type A, 19-pin female
Triggering	IP, RS-232, and built-in web server

Cable / Resolution	4K/UHD	1080p
HDMI IN / OUT	15 ft (5 m)	30 ft (10 m)
Cat 6a / 7	330 ft (100 m)	330 ft (100 m)
SFP+ (fiber)	6.2 mi (10 km)	6.2 mi (10 km)

Buttons and Indicators	
RESET (button)	1 × momentary, recessed
PWR, STATUS, VIDEO, LINK, RJ45, SFP+	6 × LED, green
DIP switches	1 × 4-position DIP, 2-pole, piano

Connectors	
OUTPUT	1 × HDMI, Type A, 19-pin female
INPUT	1 × RJ45 1 × SFP+ cage, female
RS-232	1 × 3-pin captive screw
LAN	1 × RJ45, 1000Base-T
AUDIO OUT	1 × 5-pin captive screw, balanced / unbalanced, 2-channel
IR IN / IR OUT	1 × 5-pin captive screw
48V / 0.83A	1 × 2-pin captive screw

Environmental	Fahrenheit	Celsius
Operating Temperature	+32 to +122 °F	0 to +50 °C
Storage Temperature	-4 to +140 °F	-20 to +60 °C
Operating Humidity (RH)	20% to 90%, non-condensing	
Maximum Operating Altitude	2000 m	

Power	
Consumption	Idle: 8.2 W Operating: 10.14 W Maximum: 10.14 W
BTU/h	Idle: 27.96 Operating: 34.58 Maximum: 34.58
External Power Supply (optional)	AT-PS-48083-C

Dimensions (H × W × D)	Inches	Millimeters
Unit	0.98 × 8.46 × 5.51	25 × 215 × 140
Power Supply	1.38 × 4.45 × 1.93	35 × 113 × 49

Weight	Pounds	Kilograms
Device	2.76	1.25

Certifications	
Device	CE, FCC, RoHS
Power Supply	CE, FCC, RoHS, CCC, CB

Compliance	
NDAA-889	Yes

Manufacturer	Product
Atlona	AT-SFP-PLUS-10GE-SR
FS	FS SFP+ 10GB 850nm LC
Ubiquiti	UACC-OM-MM-10G-D-2
Proline	EW3D0000710-PRO
StarTech	455883B21ST

Warranty	
Device	To view the product warranty, visit: hallresearch.com/warranty

(1) Signals can be transported over copper or fiber, but not both simultaneously.

(2) Fiber optic module for SFP+ cage is a separate purchase.

(3) Local powering will be required when SFP+ is used to extend AV signals over fiber.

© 2026 Hall Research, Inc. All rights reserved. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.
HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. Dolby, Dolby Atmos, Dolby Vision, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation. DTS, the Symbol, DTS and the Symbol together, and

Digital Surround are registered trademarks and/or trademarks of DTS, Inc. SDVoE is a trademark of the SDVoE Alliance. Velocity is a trademark of Atlona Inc. All other trademarks are the property of their respective owners.