

The Anyview 500R C-Arm offers vivid Images, innovative technology and unprecedeted value. With intelligent low dose reduction, automatic brightness control and advanced pulse technology the new Anyview 500R is a cost-effective alternative to popular C-ARMS. Save money without sacrificing technology when you choose the Anyview 500R.



Anyview 500R Mobile C-Arm

Excellent radiographic imaging
at an economical price

The Anyview 500R Surgical Mobile C-Arm combines innovation and ease of use, making it the ideal option for a variety of applications.

- ✓ T9 or 12-inch High Resolution Image Intensifier
- ✓ Reduce radiation doses with pulse frequencies of 8, 15 or 30.
- ✓ Produces up to 30 frames per second in any imaging mode
- ✓ Kv and mA settings automatically optimize to the appropriate setting for each body part.
- ✓ Dual control panels allow clinicians to operate the C-arm from both sides of the unit.
- ✓ Intelligent Dose Reduction automatically reduces dosage without sacrificing image quality
- ✓ Tethered footswitch allows hands free imaging and image capture
- ✓ Dap software easily stores patient dose information and images
- ✓ DICOM 3.0 and PACS capable
- ✓ Stored Images on hard drive can be emailed, transferred to USB/DVD or local printer/network

C-Arm Comparison

Why Spend More?



| | Anyview 500R | OEC 9800 | OEC 9900 Elite | Philips BV Pulsera |
|--------------------|-----------------|-----------------|-----------------|--------------------|
| X-ray tube anode | Rotating | Rotating | Rotating | Rotating |
| Radiographic mode | ✓ | ✓ | ✓ | ✓ |
| Fluoroscopic mode | ✓ | ✓ | ✓ | ✓ |
| 17 kW @ 100 kVp | ✓ | ✓ | | |
| Pulsed fluoroscopy | ✓ | ✓ | ✓ | ✓ |
| Pulses per second | 8, 15, 30 | 1, 2, 4, 8 | 1, 2, 4, 8, 15 | 30 |
| ABS control | ✓ | ✓ | ✓ | BodySmart |
| Snapshot mode | ✓ | ✓ | ✓ | Standard |
| Cine | 30 fps | 30 fps | 30 fps | Standard |
| Reverse position | ✓ | ✓ | ✓ | ✓ |
| Warranty | 2 year | 1 year | 1 year | 1 year |
| C-Arm Measurements | | | | |
| Free space | 31" | 31" | 31" | 30" |
| Depth | 27" | 26" | 26" | 24" |
| Orbital rotation | 135° | 148° | 115° | 135° |
| Horizontal travel | 8" | 8" | 8" | 8" |
| Vertical travel | 19.7" | 18" | 18" | 19.3" |
| Panning motion | 12.5° | 10° | 10° | 10° |
| Pivot rotation | 360° | 360° | 360° | 360° |
| Dimensions | 70" x 32" x 71" | 69" x 33" x 79" | 69" x 33" x 79" | 76" x 32" x 70" |
| Weight | 552 lbs | 720 lbs | 606 lbs | 683 lbs |