

Avante Transport 5000 Plus

Portable Anesthesia Machine

Anesthesia system with integrated safety functions

The compact Avante Transport 5000 Plus is a portable anesthesia system designed for office-based surgery centers and small facilities in which space is at a premium.

GAS SUPPLY

- › Pipeline gas: O₂
- › Output pressure of regulator: 280 kPa - 300 kPa
- › Security valve discharge pressure: ≤ 600 kPa
- › Pressure of pipeline inlet: 280 kPa - 600 kPa

FLOWMETER

- › Gas: scale
- › O₂: 0.0 L/min ~ 10 L/min
- › Precision: At 20, atmospheric pressure is 101.3 kPa, the precision of flowmeter is level: 2.5
- › O₂ flushing: 35 L/min ~ 75 L/min

RESPIRATION SYSTEM

- › Absorbent: 1000 mL
- › System leakage: When pressure is lower than 3 kPa, ≤ 125 mL/min
- › System compliance: ≤ 4 mL/kPa
- › Resistance of ventilator system:
 - › Flow-rate: 30L/min <0.16kPa
 - › Flow-rate: 60L/ min <0.52kPa
 - › APL valve ~0.19 - 6 kPa



SPECIFICATIONS



Weight:
45 lbs (20 kgs)



Length:
11.41" (29 cm)

Width:
19.29" (49 cm)

Height:
20.47" (52 cm)

520-2022-06-06