



Certified Refurbished



### ► Specifications

- Battery: 12 volt, 3.2 ampere-hour sealed lead-acid
- Battery Life: Approx. 6 hrs. with one pump running at a rate from 1 to 1400 mL/hr. Approx. 4 hrs. with both pumps running at rates from 1 to 1400 mL/hr
- Battery Recharge: 8 hrs for more than 80% recharge
- AC Power Requirements: 110/120 V, 60 Hz
- Power Cord: 2.9 m (9.5 ft.) long, with hospital grade plug
- Fuse: 0.8 A, 250 V, SB, 5.2 mm x 20 mm
- Leakage Current: Less than 50 microamps
- Weight: 17.9 lbs. | 8.1 kg
- 13"W x 5.1"D x 11.4"H | 33 x 13 x 29 cm
- Flow Range:
  - Primary program for each pump: 1.0-99.9 mL/hr in 0.1 mL increments or 1-1999 mL/hr in 1 mL increments.
  - Secondary program: 1.0-999 mL/hr in 1 mL increments or 1-999 mL/hr in 1 mL increments
  - VTBI Range: 1.0-99.9 mL in 0.1 mL increments or 1-9999 mL for both primary and secondary of each pump

## The **standard** in infusion pump technology

The FLO-GARD 6301 volumetric infusion pump is an industry standard in standard set infusion pump technology.

### Features

The Baxter 6301 is a dual-channel volumetric infusion pump. Once volume and time are selected, flow rate calculation is automatic in this model. The incremental flow rate can deliver 1-99.9mL per hour in increments of 0.1mL per hour. A computer interface allows remote operation and monitoring.