

The standard for capturing crystal clear digital video.

Features a range of digital and analog outputs.



Certified Refurbished



Technical Specifications

Imaging System	1/3" Interline Transfer, EX view HAD CCD 752 (H) x 582 (V) pixels	Signal to noise ratio	72 dB
Video Outputs		Mounting	C-mount/standard
• Composite	PAL standard	Minimum illumination	< 1.0 Lux
	1.0V P-P into 75 Ohms	Auto Shutter Range	1/50 - 1/50000
• Connector	BNC Coaxial	Gain	4 levels / 0 - 15 dB
• Component	S-VHS	Power consumption	Approx. 30 W
	Y-1.0V P-P C-0.29	Input voltage range	230 +/- 10 VAC 50/60 Hz
• Connector	4-Pin VHS	Total shipping weight	13 lbs. (5.9 kg)
• Component	RGB (or Y, B-Y, R-Y)	Dimensions	
	1.0V P-P into 75 Ohms	• Camera control Unit	9.8" / 24.8 cm (w) x
• Connector	8-Pin DIN		4.0" / 10.1 cm (h) x
• Digital Visual Interface	(DVI) Digital 1024 x 768 XGA resolution, 29-Pin DVI-I	• Camera head to camera control unit	10' / 3 m
• Serial Digital Interface	Digital SMPTE-259M BNC coaxial XGA analog		sealed cable or
Resolution	950 lines		21.3' / 6.5 m sealed cable (sensed by CCU)
		Enhancement	Switchable to 8 steps
		Cable connector	Super lemo gold pin connectors