

Provides outstanding illumination across all endoscopy applications.

The Stryker Endoscopy X-6000 Xenon Light Source is a high performance device designed for use with Stryker Endoscopy medical video cameras to provide outstanding illumination of the surgical site across all endoscopic applications. With the proper light cable and adapters, it can be connected to any flexible or rigid endoscope.



The X-6000 is equipped with a special safety feature that, when using an ESST cable, will prevent accidental burning caused by an unattended light cable. Electronic Scope Sensing Technology senses when the scope and the light cable are separated and places the light source in standby.



Technical Specifications

Electrical		Transportation & Storage	5 to 40° C
• Primary	100 - 240VAC 50/60 Hz 450W		10% to 85% Relative Humidity
• Fuse	8.0A 250V		700hPa to 1060hPa
Fiber Optic Cable Range	2 mm to 11.5 mm outside diameter continuously adjustable	Classifications & Approvals	Complies with IEC 601-1 with Amendments 1 & 2, CSA Std. C22.2 No. 601.1-M90, and UL2601-1. Complies with EN 60601-1-2: 1993 (EMC Compliance of Medical Devices) Class 1 Equipment Type CF applied parts
Dimensions	38.1 cm (w) x 41.4 cm (d) x 14 cm (h) 15.0 in. (w) x 16.3 in. (d) x 5.5 in. (h)	Patent Protection	U.S. #5,850,496 and 6,110,107. Other patents pending
Weight	10.9 Kg		
Lamp	300 Watt Xenon Cermax		
Lamp Life	Approximately 500 hours		
Operating Conditions	5 to 40° C 10% to 85% Relative Humidity		