



# S7.5

## ➤ General

- Throw 50m
- Aerodynamic composite lightweight cone
- Standard horizontal oscillation
- Hot dipped galvanized structure
- Low noise high efficiency fan
- Adjustable angle of throw -10° to 50°
- Integrated water filter system

## ➤ Water specifications

- A constant inlet press. of 1,5 bar with the rated flow
- Stainless steel booster pump
- Waterbox filtersystem with flushfunction
- Waterhose with 1" BSP male fitting
- Stainless steel nozzling
- Quick change stainless steel nozzle
- Last chance filter before nozzle
- Droplet size spectrum vary from 50 to 150 µm
- Waterflow 2700l/h

## ➤ Electrical specifications

- Voltage 3x400V 50Hz
- Fan (kw) 7,5 (softstarted)
- Pump (kw) 4
- Rot. (kw) 0,09
- IP66 steel cabinet

## ➤ Options

- Pressure/level detection
- Membrane valve
- Splittable nozzling (-50% waterflow)
- Remote control
- Electric vertical movement
- Fixed angle detector
- Stainless steel cabinet
- Wheelset
- Heating package
- Phase controller
- Saltwater package connectors
- Auto waterdrain valve
- Extra epoxy coating
- Dosage pump
- Feeding pump
- UV-filter

## ➤ Dimensions and weight

- Length 1550 mm
- Width 1600 mm
- Height 2250 mm
- Weight 450 kg

## Spraystream

Standard machines



*The Spraystream S7.5 is a dust suppression machine that generates a consistent stream of microdroplets to capture airborne dust particles and prevent the escape of fugitive dust.*

This type belongs to the range of more giant misting cannons and is mainly used for **outdoor misting**. The machine is available mobile but can also be mounted. This type is very suitable for **demolition work**. The device can be used for dust- or odour suppression.

