




 **label it**[®] **560**
PRINT & APPLY

- Production (m/min): 30 ppm
- Minimum size (mm): 30x30
- Maximum size (mm): 150x210 (6")
- Standard piston: 250 mm



Piston
applicator

Description

- Equipment for automatic labelling of self-adhesive labels on the top, side or bottom side of unitary product or boxes.
- Print and Apply.
- Manual height adjustment using a steering wheel, which can be optionally motorized.
- Structure built in protected steel, anodized aluminum that brings great weight and rigidity to the machine.
- Robustness and reliability suitable for demanding conditions.
- Electric cabinet supported on the structure.





TECHNICAL DATASHEET

COMPONENTS

PRINTERS	CL4NX, CL6NX
CONTROL	PLC SIEMENS S7-1200
INTERFACE	4:3" HMI TOUCHSCREEN
CONTROL PANEL	CABINET MOUNTED ON THE STRUCTURE
CONSTRUCTION	PROTECTED STEEL AND ANODIZED ALUMINIUM
TRACTION LABEL	PRINTER
APPLICATION	PISTON
BEACON	VISUAL (2-COLOURS)
HEIGHT REGULATION	MANUAL

CAPACITY

PRODUCTION	ACCORDING TO CONFIGURATION
LABELLING	REAL
MAX. WIDTH LABELLING	6" (OPTION)
APPLICATION	SUPERIOR OR SIDE
LABELLING HEIGHT	1000 MM
WORKING SENSE	RIGHT/LEFT
UNWINDER	OUTSIDE/INSIDE Ø200 MM – Ø75 MM
REWINDER	PRINTER

COMMUNICATIONS

INPUT SIGNALS	START (PRESENCE)
OUTPUT SIGNALS	THE MACHINE IS NOT OK/APPLICATION OK
DATA INTERFACE	ETHERNET, RS-232, PARALLEL

OPTIONS

CHECK READER	READABLE BARCODE CONTROL
VERIFIER READER	7" TOUCH SCREEN
NOTICE	END OF LABELS
MAX. WIDTH LABELS	IN FUNCTION OF CUSTOMER NEEDS
BEACON	ACOUSTIC AND VISUAL BEACON (3-COLOURS)
REGULATION HEIGHT	MANUAL OR MOTORIZED 250 MM. POSSIBILITY OF DIFFERENT HEIGHTS
CONSTRUCTION	STAINLESS STEEL
PRINT WIDTH	6"

REQUIREMENTS

POWER SUPPLY	220VAC +-10%, 50HZ
CONSUMPTION	1A
INSTALLED POTENCY	0,5KW
COMPRESSED AIR	6 BAR - 150 L/MIN
DIMENSIONS	1100 X 1100 X 2000
WEIGHT	120 KG
PERMISSIBLE WORKING CONDITIONS	5°C-35°C HUMIDITY 20%, 90% NON-CONDENSED

