



YES ELECTROMOTIVE

CAMPUS TRANSIT®

GEN 1 & 2



Specification

TYPE	GEN 1	GEN 2	SALIENT FEATURES
Electric Motor			Drive & Safety
Electric Motor Type	Permanent Magnet	Permanent Magnet	Laminated tempered glass windscreen
Electric Motor Rated Power (kW)	5, 8	10	Onboard charger
Battery			LED headlights
Type	Lithium Ferro Phosphate (LFP)	Lithium Ferro Phosphate (LFP)	Front Disk & Rear Drum brakes
Capacity (kWhr)	13.5 17.5	22	Reversing Camera
Range (km)	100 130	150	Comfort & Convenience
Drive Type			Spacious modern design
Drive	Rear Wheel Drive	Rear Wheel Drive	Comfortable padded seats
Grade Ability	20% (with Full Load)	20% (with Full Load)	Easy to clean & disinfect interior surfaces
Wheel Size	12"	12"	Optional
Weight & Capacities			Electronic Power Steering
Curb Weight (including Battery)	960 kg	1100 kg	Additional (second) battery
Seating	Driver + 10 Driver + 13	Driver + 10 Driver + 13	Pack Daytime Running
Payload	1000 kg	1000 kg	Lamp Fog Lamps

Dimensions



Width (mm) 1550



Length (mm) 4500



Height (mm) 2050

The above values are results from internal testing and are subject to change after validation.
Some of the equipments illustrated or described in this catalog may not be supplied as standard equipment and may be available at extra cost.
YES Electromotive (SMC-Private) Limited reserves the right to change specifications and equipments without prior notice.
The color plates shown may vary slightly from the actual color due to limitations of the printing process.

Upgrades in Gen 2

Larger Battery Pack: Now offering a 50% boost in energy and power for delivery for a long range

Increased motor power: Enjoy 20% upgrade in motor-rated power, complemented by a highway grade rear axle for enhanced performance.

Advanced voltage system: Upgrade from 72V to 96V, featuring a CAN bus architecture for more efficient communication and control.



YES ELECTROMOTIVE

552 C, Sundar Industrial Estate, Lahore, Pakistan
+92 310 704 1111, info@yeselectromotive.com
www.yeselectromotive.com