

TW CONNECTOR



TW30 Series



▲ TW30M / TW30F

▲ TW30M-W

▲ TW30F-B

▲ TW303M / TW303F

▲ TW303P Sheath

TW60 Series



▲ TW60M / TW60F

▲ TW60M-P

▲ TW603F / TW603M

▲ TW60M-H / TW60F-H

▲ TW60M-B

▲ TW60-H Female/Male Sheath
TW603P Sheath

TW90 Series



▲ TW90M / TW90F

▲ TW90M-B

▲ TW90F-B

Female & Male Copper Pin



▲ TW600 (F-pin)
TW601 (M-pin)

▲ TW900 (F-pin)
TW901 (M-pin)
4.5mm

Customized Strain Relief + cable



▲ TW60F+128mm 10AWG
TW60M+150mm 12AWG

TW Series	TW30	TW60	TW90	TW600 & 601	TW900 & 901
Dielectric Withstanding Voltage	500VDC				
Current Capacity	20A	50A	90A	50A	90A
Inrush Current Capacity	30A	60A	120A	60A	120A
Contact Resistance	10mΩ MAX	20mΩ MAX	20mΩ MAX	-	
Op. Temp.	-20~120°C	-20~120°C	-20~120°C	-	



High Compatibility
Drop-in replacement for XT30/XT60/XT90 connectors, enhancing application flexibility.



Patented Technology
Patent M667881 guarantees technical advantages and product uniqueness.



Safe & Reliable
High-temperature design supports high current load; meets RoHS/REACH requirements.