ERREQUADRO

Unlock the power of technical data












WHAT IS KYD®?

KYD® (Knowledge in Your Data) is a **modular software** designed to analyze companies' internal **technical data** to exploit their knowledge and avoid reinventing the wheel (e.g. RFQ – Requirements).



WHAT IS KYD®?

KYD[®] (Knowledge in Your Data) has been developed to help companies **analyzing** their **data and get information from it**.

In the context of PoC projects Erre Quadro can design simple UI for validation purposes only.

Data entry

Data management

Data analysis

Data interpretation

Data visualization*

*for PoC/validation purposes only.

The RFQ process

Transform the request in Requirements

1. A new request arrives. Sales teams usually have to ask Clients for clarifications. In this phase they tend to involve technical departments so to collect the right questions to ask in order to collect adequate and complete Requirements.



Retrieve internal knowledge

2. Sales teams ask technical departments to assess the technical feasibility and formulate a valuable proposition. This usually implies the analysis of all the documentation sent by the Client and long design sessions.



Create the quotation

3. Once the technical proposition has been defined, technical departments and Sales teams collaborate on the final quotation. This usually implies multiple iterations.

The common process can take weeks or even months before completion and lacks in scalability.

The RFQ process with KYD®

Transform the request in Requirements

1. KYD® supports Sales teams by retrieving those past conversations with the technical departments that are more correlated to the Client's request. This in turn reduces the number of low-value interactions with the technical departments and the overall time needad.



Retrieve internal knowledge

- 2. KYD® analyses the documentation and extracts:
 - Technical parameters
 - Norms and standards
 - Tests on materials
 - .

It then retrieves the past projects and quotations that better correlating with the retrieved technical requirements



Create the quotation

3. KYD® matches the extracted requirements with past projects and quotations, thus maximizing the reuse of companies' internal knowledge.

Business cases



The RFQ process with KYD®: three business cases

Extract the Retrieve internal Create the quotation Requirements knowledge A search engine to support Sales teams in retrieving past e-mail threads and quotations 3

Client / Sector: Medium Enterprise / Industrial analytical laboratory

Problems

- Too much time to respond to Clients requests (1 week ÷ 1 months)
- Too many useless interactions between Sales and Engineering
- No reuse of corporate's knowledge (constantly reinventing the wheel)

Technical context

- Absence of a structured CRM
- Presence of a structured db of past quotations
- Documents features
 - High standardization
 - .pdf; .json



Client / Sector: Medium Enterprise / Industrial analytical laboratory


Solution

Search engine



Client / Sector: Medium Enterprise / Industrial analytical laboratory


Solution



Client / Sector: Medium Enterprise / Industrial analytical laboratory

Solution

Search engine



Client / Sector: Medium Enterprise / Industrial analytical laboratory

Project highlights

- Time to delivery: 3 months
- The Client has been involved in the first phase consisting in the codesign of the UX
 - Client's effort: 0,5 day
- In a second phase, the search algorithms have been tuned exploiting a training set of 100 docs.
 - Client's effort: 2 days

Project results

- Average response time lowered: -80%
- Average number of interactions with tech. dep.: -50%



The RFQ process with KYD®: three business cases

Extract the Requirements

Retrieve internal knowledge

Create the quotation

A search engine to support Sales teams in retrieving past e-mail threads and quotations

A UI to support assign tenders and retrieve most similar past projects

3

Client / Sector: Big Company / Architecture

Problems

- Too much time to assign tenders to internal staff (1 week ÷ 1 months)
- Scarce reuse of corporate's knowledge (constantly reinventing the wheel)

Technical context

- Data entry already covered
- Presence of a structured db of past projects
- Documents features
 - High standardization
 - .pdf; .json



Client / Sector: Big Company / Architecture

Solution


• Classification software + search engine + matchmaking



Client / Sector: Big Company / Architecture

Solution

Classification software + search engine + matchmaking



Client / Sector: Big Company / Architecture

Solution

- Classification software + search engine + matchmaking
- 4. The user can select one or more of the taxonomical classes. The search engine will retrieve all the corresponding tenders from the db

 Serverulo sulla pattaforma KYO (Knowledge in Your Data)


 Sicros document of gars mediante fifto sull ontologia, incercando per parole chiave nel search engine o trascinando un nuovo disciplinare di gars in formato pel

 Cortology

 Cortol

Client / Sector: Big Company / Architecture **Solution**


Classification software + search engine + matchmaking



Client / Sector: Big Company / Architecture

Solution

• Classification software + search engine + matchmaking



Client / Sector: Big Company / Architecture

Project highlights

- Time to delivery: 3 months
- The Client has been involved in the first phase consisting in the co-design of the taxonomy and UX
 - Client's effort: 2 days
- In a second phase, the matchmaking algorithms have been tuned exploiting a training set of 100 docs.
 - Client's effort: 4 days
- In a third phase, the software has been released and validated by the Client after 15 days of trial.

Project results

- Average time needed to assign tenders internally lowered: -95%
- Average time needed to recover past projects lowered: -80%



The RFQ process with KYD®: three business cases

Extract the Requirements

Retrieve internal knowledge

Create the quotation

A search engine to support Sales teams in retrieving past e-mail threads and quotations

A UI to support assign tenders and retrieve most similar past projects

A software that retrieves technical requirements from tenders and correlates them with products specifications and past projects.

3


Client / Sector: Multinational corporation / Automotive

Problems

- Too much time spent to generate quotations for tenders (1 week ÷ 2 months)
- Scarce reuse of corporate's knowledge (constantly reinventing the wheel)

Technical context


- Data entry already covered by the Client
- Presence of a structured db of product specifications
- Documents features
 - Medium standardization
 - .pdf; .json
 - Data of interest reported within tables and/or images



Client / Sector: Multinational corporation / Automotive

Solution

Technical entity recognition + matchmaking




Client / Sector: Multinational corporation / Automotive

Solution

Technical entity recognition + matchmaking


2. The platform automatically extracts a predetermined set of requirements from selected document and fills the requirements table.



Client / Sector: Multinational corporation / Automotive

Solution


Technical entity recognition + matchmaking



Client / Sector: Multinational corporation / Automotive

Solution


Technical entity recognition + matchmaking



Client / Sector: Multinational corporation / Automotive

Solution

Technical entity recognition + matchmaking



Latching Efforts (No beat)

900N, 8890N, 9000N, 4500N, 1000N, 11110N, 4450N, 440N, 8100N, 5625N, 5620N, 11110N, 4450N, 440N, 8100N, 5625N, 5620N, 11110N, 4450N, 5620N, 1110N, 4450N, 5620N, 5	Extraction 1	Extraction 2 Extraction 3 Project 1 Project 2 Project 2 Project 3								
1000N, 11110N, 4450N, 440N, 8100N, 5625N, 6000N, 111250N		LAU action_2	Extraction_3		Project 1	Project 2	Project 3	Project 4	Project 5	_
Static Tensile Durability 1.00 0.58 0.69 0.54 0.96 0.75 0.90 0.71 0.62 0.75 0.75 0.75 0.75 0.75 0.75 0.75 0.75	,,			Global	0.91	0.76	0.72	0.65	0.61	
Durability 1.00 0.94 0.78 0.83 0.99	,			Static Tensile	1.00	0.58	0.69	0.54	0.96	
Striker 0.81 0.35 0.92 0.82 0.61 V: 45000 V: 45000 V: 22500 Imperature RT 80°C -35°C V: 45000 V: 22500 V: 45000 V: 22500 V: 22500 V: 45000 V: 22500 V: 45000 V: 45000 V: 22500 V: 45000 V: 22500 V: 45000 V: 45000 V: 22500 V: 45000 V: 450	,,			Durability	1.00	0.94	0.78	0.83	0.99	
V: 45000 V: 7500 CV: 22500 CV: 22500 CV: 22500 CV: 2500 C	,			Striker						
V: 7500 CV: 22500 emperature RT 80°C -35°C 7.0 0.70 0.22 0.85 0.78 0.77 0.93 0.70 0.98 0.62 0.67 1.00 0.61 0.60 0.71 0.62 1.00 0.80 0.55 0.51 0.80 1.00 0.80 0.74 0.78 0.78 0.79 0.80 0.90 0.80 0.90 0.80 0.90 0.80 0.90 0.80 0.90 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80 0.80				Diameter	0.81	0.35	0.92	0.82	0.61	
1.00				Distance						
######################################					0.70	0.22	0.85	0.78	0.77	
7.0 1.00 0.61 0.60 0.71 0.62					0.70	0.22	0.85	0.76	0.77	
/-0.5mm, 0.5mm /-0.5mm	7.0				0.02	0.70	0.00	0.62	0.67	
/-0.5mm					0.93	0.70	0.96	0.02	0.07	
7-5.5mm OT PRESENT inching latch: 650N (RT), 20N (80°C), 830N (-35°C) E-latch, Mechanical latch: 530N (RT), 430N (80°C), 690N (-35°C) 530N (RT), 430N (80°C), 690N (-35°C)	/-0.5mm, 0.5mm				1.00	0.61	0.60	0.71	0.62	
1.00 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.51 0.80 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55 0.55	/-5.5mm									
inching latch: 650N (RT), 20N (80°C), 830N (-35°C) .5Nm at RT, 6.3Nm at 80°C, .38m at -35°C .5Shg, 400G, 50G complete the perature (RT) 23	OT PRESENT				1.00	0.80	0.55	0.51	0.80	
20N (80°C), 830N (-35°C) .5Nm at RT, 6.3Nm at 80°C, .3Nm at -35°C 27G, 285G, 400G, 50G com temperature (RT) 23 C± 2°C Ct 2		E-latch, Mechanical latch:								
(-35°C) .5Nm at RT, 6.3Nm at 80°C, .3Nm at -35°C 27G, 285G, 400G, 50G oom temperature (RT) 23 Storage temperature range - Operating temperature range C± 2 °C 40°C to +90°C -35°C to +80°C 0.96 0.90 0.65 0.93 0.84 0.84 0.63 0.98 0.69 0.62 0.84 0.63 0.98 0.69 0.62 0.90 0.62 0.90 0.62 0.84 0.63 0.98 0.69 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.63 0.98 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.62 0.90 0.63 0.98 0.90 0.62 0.90 0.63 0.98 0.90 0.62 0.90 0.62 0.90 0.65 0.90 0.65		530N (RT), 430N (80°C), 690N			0.30	-0.04	0.66	0.74	0.78	
3.3Nm at -3.5°C	20N (80°C), 830N (-35°C)	(-35°C)		Labelong						
27G, 285G, 400G, 50G oom temperature (RT) 23 Storage temperature range - Operating temperature range - 35°C to +80°C Operating temperature range - Operating temperature range - 35°C to +80°C Operating temperature range - Operating temperature	.5Nm at RT, 6.3Nm at 80°C,			Efforts (No.	0.96	0.90	0.65	0.93	0.84	
com temperature (RT) 23 Storage temperature range - 40°C to +90°C Operating temperature range - 35°C to +80°C Temperature - 0.56 0.44 0.90 0.54 0.70 Voltage 1.00 0.89 0.61 0.70 0.81	.3Nm at -35°C			Seof)						
±2.°C 40°C to +90°C -35°C to +80°C Voltage 1.00 0.89 0.61 0.70 0.81	27G, 285G, 400G, 50G			hertal 5	0.84	0.63	0.98	0.69	0.62	
Voltage 1.00 0.09 0.01 0.70 0.01		Storage temperature range -	Operating temperature range	Temperature	0.56	0.44	0.90	0.54	0.70	
C O I I I I I I I I I I I I I I I I I I		40°C to +90°C	-35°C to +80°C	Voltage	1.00	0.89	0.61	0.70	0.81	
Current	C 9V~16V			_						
to 30mA 0.89 0.59 0.86 0.98 0.96	to 30mA				0.89	0.59	0.86	0.98	0.96	Ų

♦ Log out


Client / Sector: Multinational corporation / Automotive

Project highlights

- Time to delivery: 6 months
- The Client has been involved in many phases, including creating training sets and validating the results.
 - Client's effort: 1 month
- In a final phase, the software has been released and validated by the Client after 1 month of trial.

Project results

- Average time needed to analyse tenders: -95%
- Number of human errors lowered: -20%



Contacts

- O Largo Padre Renzo Spadoni 56126 Pisa



