

www.cleverfilter-group.com

Filter Bags – Needle felt PPSG, PPE, PPX and PESG, PEE, PEX series

CleverBag

Non-Woven Felt with Seal Ring

Features

- FDA compliant
- Free from crater forming substances (i.e. silicone)
- Available as single- and multi-layered bags with graded pore depth structure
- 1 μm 200 μm nominal retention rates
- PP, PE or metal ring as bag sealings
- Excellent chemical compatibility
- Thermal surface treatment effectively minimizes fibre migration
- Recommended change out pressure differential
 0.1 0.16 MPa (1.0 1.6 bar)
- TQM for a consistently reliable quality

Benefits

- Easy Installation no tools required
- Double Sealing plastic collars designed to provide additional safety against bypasses
- Stable Material Composite both stable and flexible filter bags for better alignment to the restrainer basket
- Available Sizes all standard but also customized sizes for an optimal process adaptation
- High Dirt Capacity to ensure a long lifetime
- Low Disposal Cost to further improve economics



Applications

- Automotive Industry
- Water Treatment
- Pharmaceutics
- Food and Beverage
- Chemical Industry
- Paints and Varnishes
- Many Others



www.cleverfilter-group.com

Product Categories: Needle Felt Filter Bags, Non Woven

1.	PPSG	Polypropylen	Standard
2.	PPE	Polypropylen	double layer
3.	PPX	Polypropylen	triple layer
4.	PESG	Polyester	Standard
5.	PEE	Polyester	double layer
6.	PEX	Polyester	triple layer

Technical Data

Sizes	Filter Material	Seam Treatment	Length [mm]	Ø [mm]	Filter Area [m²]	Volume [l]	Housings, e.g.
size 1	PP, PE	welded or stitched	420	180	0.25	8.0	HEXB23, HTWB23
size 2	PP, PE	welded or stitched	820	180	0.50	17.5	HEXB45, HTWB45
size 3	PP, PE	welded or stitched	230	100	0.09	1.5	HEXB6, HTWB6
size 4	PP, PE	welded or stitched	380	100	0.15	2.5	HEXB10, HTWB10
size 5	PP, PE	welded or stitched	510	150	0.25	8.0	HPPB23, HSSB23

Product Code

PESG - 100 - WS - SS 2

Material:

PPSG: PP needle felt standard
PPE: PP needle felt double layer
PPX: PP needle felt triple layer
PESG: PE needle felt standard
PEE: PE needle felt double layer
PEX: PE needle felt triple layer

Retention rate nominal [µm]:

1;3;5;10;25;50;75;100;125;150;200

WS: welded seam SE: stitched seam

Bag size Ø * L [mm]:

1:180 * 420 2:180 * 820 3:100 * 230 4:100 * 380 5:150 * 510

Bag sealing:

SS: galvanised carbon steel ring

ST : stainless steel ring
PLK : PP plastic collar
ELK : PE plastic collar
PD : PP plastic collar
(size 5 only)

Other types on request.