

# Let's deorbit your spacecraft together!

### Why using a deorbit sail?

Stay compliant with the 5-year deorbit rule using our commercial, flight-proven ADEO dragsail. It is compact, lightweight, cost efficient, easy to integrate, works


without any propellant and can be chosen as primary or secondary deorbit solution:


ADEO as baseline: Because no launch is no option!

ADEO as risk mitigation backup: Be fail-safe through redundancy!

Optional add-on upon request: In case of a satellite failure, ADEO can autonomously deploy to safely deorbit your spacecraft – helping you to avoid regulatory penalties.







#### **Interested in ADEO?**

Contact us:

HPS GmbH Hofmannstr. 25-27 81379 Munich, Germany

+49 89 45 20 576-0adeo@hps-gmbh.com

#### The ADEO Product Family













|                         | ADEO-P(ico)                   | ADEO-C(ube)                | ADEO-Nx                | ADEO-N(ano)                  | ADEO-M(edium)              | ADEO-L(arge)                      |
|-------------------------|-------------------------------|----------------------------|------------------------|------------------------------|----------------------------|-----------------------------------|
| S/C mass                | 1-20 kg                       | 5-50 kg                    | 1-30 kg                | 20-250 kg                    | 100-700 kg                 | 500-1,500 kg                      |
| ADEO mass               | 0.42 kg                       | 0.80 kg                    | 0.77 kg                | 0.80 kg                      | 4.50 kg                    | 9.50 kg                           |
| ADEO size               | 10 x 10 x 3.9 cm <sup>3</sup> | 9.4 x 9.4 x 7.2 cm³        | 10 x 10 x 9.8 cm³      | 10 x 10 x 10 cm <sup>3</sup> | 21 x 21 x 17.4 cm³         | 40.6 x 40.6 x 26 cm <sup>3</sup>  |
| Sail area               | 1.7 m²                        | 4.0 m²                     | 2.0 m²                 | 5.0 m²                       | 15.0 m²                    | 25.0 m²                           |
| Mechanism               | Spring-based                  | Spring-based               | Spring-based           | Spring-based                 | Spring-based               | Motor-based                       |
| Activation              | Pyro cutter                   | Pyro cutter                | Pyro cutter            | Pyro cutter                  | Pyro cutter                | Release nut                       |
| Mechanical<br>interface | 4 x M4<br>through holes       | Customizable               | 30 x M2.5 thread       | 4 x M5 thread                | 8 x M6<br>through holes    | 8 x 7.0 mm<br>through holes       |
| Electrical<br>interface | 2 wires<br>(free ends)        | 2 x 2 wires<br>(free ends) | 2 wires<br>(free ends) | 2 wires<br>(free ends)       | 2 x 2 wires<br>(free ends) | 3 Connectors<br>D-Sub HD15, RS422 |
| Electrical<br>power     | 12V@1A<br>10 msec             | >1V@4.25A<br>10 msec       | 12V@1A<br>10 msec      | 12V@1A<br>10 msec            | >1V@4.25A<br>10 msec       | 24-38 VDC                         |

Note: The ADEO product family is qualified for flight, some units already achieved TRL 9, and has been undergoing continuous improvement for over 10 years through numerous technology development activities. These efforts have been co-funded by ESA, DLR, the State of Bavaria, and significant internal investments, in collaboration with various companies and research institutes, including DLR and Fraunhofer.

In orbit picture of ADEO-N2 (15.12.2022) ©D-Orbit/HPS GmbH

#### **Need more information about ADEO?**

Scan the QR code or check out our website and online configurator: https://www.hps-gmbh.com/portfolio/adeo-deployable-dragsails/



## Has ADEO been flown and verified? YES, multiple times!

