



**MULTI-PATH MACHINING CENTER**

**JS-D580S-2**

## **Technical Specification**

Version 2025

SHENZHEN JOJOY SEIKO CO., LTD.  
HUIZHOU JOJOY SEIKO CO., LTD.

## General Description



Under the background of increasingly fierce competition in the modern manufacturing and machining industry, JOJOY SEIKO has creatively introduced the **Multi-Path Machining Center Series** with **an innovative and unique structural design** to help our customers significantly **reduce costs** and **increase efficiency**. It can not only effectively control the costs of purchasing, labor and land etc., but also the efficiency is even **several times higher** than that of universal machining centers of the world's top brands.

## Features

- + The main structure of machine tool is consisted of **only cast iron HT300** with high stability and rigidity.
- + **2-path design** means which can achieve **2-station simultaneous machining** to improve the efficiency heavily with relatively independent **2 spindles, 2 worktables and 2 servo ATCs**.
- + All the servo motors are equipped with absolute value bus encoders for accuracy compensation independently.
- + 4-axis or 5-axis rotary table and probe optional for customized requirements.

## Technical Data

TECHNICAL DATA	UNITS	JS-D580S-2
<b>Travel &amp; Range</b>		
X-axis Travel	mm	580*2
Y-axis Travel	mm	450*2
Z-axis Travel	mm	500*2
Distance from spindle nose to countertop	mm	140-640
<b>Worktable</b>		
Quantity	-	2
Worktable size	mm	580*420
Max. loading capacity	kg	300
T-slot (width/quantity/distance)	mm/pcs/mm	14/3/125
<b>Spindle</b>		
Quantity	-	2
Max. spindle speed	rpm	15000
Spindle taper	-	BT 30
Spindle power	kw	5.5
Drive type	-	Direct-drive
Spindle cooling system	-	Oil cooling (Opt.)
<b>Controller &amp; Servo System</b>		
CNC controller	-	SYNTEC
X/Y/Z servo motor power	kw	2.4/2.4/3.9*2
<b>Servo ATC</b>		
Quantity	-	2
Capacity	T	24T*2
Max. tool diameter	mm	100
Max. tool length	mm	200
Max. tool weight	kg	3
Tool-to-tool	s	2
<b>Feed Rate</b>		
X/Y/Z Rapid traverse	mm/min	30000
X/Y/Z Cutting speed	mm/min	10000
<b>Accuracy</b>		
X/Y/Z Positioning accuracy	mm	±0.005/300
X/Y/Z Repeatability	mm	±0.003/300
<b>Other Data</b>		
Air source required	Kgf/cm <sup>2</sup>	6.5
Gross weight	kg	5000
Overall dimension (L*W*H)	mm	2710*2425*2510
Rated power	kw	30

## Standard Accessories

ITEMS	BRAND	ORIGIN	REMARKS
CNC controller	SYNTEC	Taiwan	-
Spindle servo motor	SYNTEC	Taiwan	-
X/Y/Z servo motor	SYNTEC/INOVANCE	Taiwan/China	-
Spindle	DEJO/SPINDER	Taiwan	
Ball screw	THK/IF	Japan/Germany	Grade C3
Rolling guide	THK/REXROTH	Japan/Germany	PMI/HTPM Optional
Bearing	NACHI/NSK	Japan	-
Coupling	NBK	Japan	-
Servo ATC	OKADA/AIMACH	China	20T*2
Electrical components	SCHNEIDER	France	-
Pneumatic system	SMC	Japan	-
Lubricating system	BAOTN	China	-
Cutting coolant system	-	China	-
Chip conveyor	-	China	2 screw-type
AC for electrical cabinet	-	China	
Air through spindle	-	China	-
Electronic handwheel	-	China	-
Bottom chip flushing	-	China	-
Tool setter	-	China	Contact measurement

## Optional Accessories

NO.	OPTIONS
1	MITSUBISHI / HNC CNC controller
2	Variable spindle power/speed/torque
3	Coolant through spindle
4	4-axis / 5-axis rotary table
5	Probe for workpiece set-up & inspection
6	Chain-type chip conveyor
7	Oil mist collector
8	Oil cooler
9	Oil-water separator

## Inspection and Acceptance

In case this is the part of the contract, the Seller shall notify the Buyer of the specified time for inspection at least 30 days in advance, and the Buyer shall send a representative to the Seller's factory, before packaging the equipment, to execute it in accordance with the requirements stipulated in the contract as following:

- **Standard 3-axis simultaneous cutting test and measurement.**
- **Positioning accuracy test and measurement.**
- **Other specific and reasonable tests and measurements.**

If the Buyer's representative fails to arrive at the Seller's factory for inspection as scheduled, the contractual equipment will not be delayed in packaging and delivery. Therefore, the Buyer's representative could only complete the procedure on other equipment of the same model or be regarded as a waiver of it.

The Seller shall provide the Buyer with the inspection report obtained according to the requirements stipulated in the contract, and if the inspection results meet the requirements, it shall be deemed that the contractual equipment has passed the inspection. The Buyer and the Seller shall then sign the acceptance confirmation.

## Technical Documents

- **Operation Manual \* 1 Copy**
- **Programming Manual \* 1 Copy**
- **Mechanical Manual \* 1 Copy**
- **Electrical Manual \* 1 Copy**

## Seal and Signature

■ **The Seller**

■ **The Buyer**