



SOL PLUS collector series

SOL PLUS EVO
SOL PLUS ARGO

10
YEAR
WARRANTY

Product Benefits

- High efficiency due to intelligent product design, at the highest quality level
- Long life operation due to the use of high-quality materials
- Tempered solar safety glass
- Light weight for easy transport
- High corrosion protection due to the anodized aluminum
- Quick installation time for horizontal or vertical mounting
- The product is also available with the option of hidden ventilation



Technical data

Collector type	Type 15	Type 17	Type 19	Type 20	Type 23	Type 25	Type 27	Type 29
Overall area [m ²]	1.51	1.68	1.96	2.02	2.24	2.52	2.67	2.92
Absorber area [m ²]	1.35	1.51	1.79	1.83	2.03	2.33	2.43	2.71
L x W x H [mm]	1503x1007x103	1420x1183x103	1503x1305x103	2006x1007x103	1893x1183x103	2006x1257x103	2261x1183x103	2006x1457x103
Absorber sheet	PVD Blue Selective Aluminum							
Absorption [%]	95							
Emission [%]	5							
Ø manifold [mm]	22							
Ø risers [mm]	8 or 15							
Connections Cu Ø 22	4 or 2							
Housing	Aluminum frame							
Surface	Silver or Black anodized							
Back plate	Aluminum sheet							
Glass	3.2 mm tempered solar glass							
Transmittance of glass [%]	91 - 92							
Insulation	40 mm mineral rock wool plate							
Max. stagnation temperature	185 °C under test conditions							
Max. operating pressure	10 bar							
Proper heat transfer medium	Polypropylene glycol / water mixture							
Approved installation angle	min. 15°, max. 75°							
Packaging	Customised							
Position	Vertical or Horizontal							



11.000m² production facilities

500.000m² annual capacity

42 years of experience

2nd km Argos-Nafplio | 21200, Argos, Greece

tel: +30 27510 20920-2

sales@dimas-solar.gr

www.dimas-solar.gr