

QUAVA Spot

- Designed for super fine cleaning
- Remote control function added
- CE certified



29110 (QT-021CE), CE

ULTRASOUND CHARACTERISTICS

- Ultrasonic output power of 100W and 50W
- Working frequency of 200kHz, 430kHz, 950kHz and 2MHz/3MHz
- PLL and A mode selectable oscillation modes

OPERATING SYSTEM

- Output adjustment by increments of 0.1W
- Real-time active output power display
- Status and errors display
- Various cleaning fluids can be used

TECHNICAL DATA

- Power supply 100V to 240V
- Single phase of 50/60Hz
- Generator dimensions: 218x 158 × 138 mm
- Generator weight: 5Kg

REMOTE CONTROL MODE

- Remote Terminal
- RS-485
- Device Net



semiconductor products



LED FPD



HDD parts



Mechanical parts



Clock parts



Medical instruments



Food products



Glasses & Lenses

SPOT SHOWER



Model	27220	17220	28220	29220	29220H
Generator	30110 (QT – 023CE)		29110 (QT – 021CE)		
Input	50W	20W	30W	30W	30W
Frequency	430kHz		950kHz	2MHz	3MHz
Flow	2-3.5 ^l / _{min}	1-2 ^ℓ / _{min}	1-1.5 ^l / _{min}	1-1.5 ^l / _{min}	1-1.5 ^ℓ / _{min}
Dimensions	Ø57×90 mm	Ø36×71 mm			


 Effective cleaning is achieved on fragile surface cleaning objects.


MEGA TUBE




Model	27222	17222	28222		
Generator	30110 (QT – 023CE)				
Input	50W	20W	30W		
Frequency	430	950kHz			
Flow	$2-3.5^{\ell}/_{min}$	1-2 [{] / _{min}	1-1.5 [{] /min		
Dimensions	Ø57 × 90 mm	Ø36 × 71 mm			

The ultrasonic energy in the cleaning liquid is sprayed through the quartz tube.







Kaijo Quava Spot – designed for superfine cleaning of HDD media, FPD glass, semiconductor wafers and semiconductor processing components.



URL KAIJO SHIBUYA EUROPE GMBH https://kaijo-shibuya.de

KAIJO CORPORATION