



NAVI PLUS tray collector series

NAVI PLUS EVO NAVI PLUS ARGO

10 YEAR



Product Benefits

- New tray design with advanced engineering, ensuring high efficiency, combined with high durability
- The robot-automated production line ensures the highest level of precision and sealing
- Long life operation due to the use of highquality materials
- Tempered solar safety glass with black frame design, ensuring high aesthetics
- Light weight for easy transport and installation handling
- Quick installation time for horizontal or vertical mounting





NAVI PLUS tray collector series

Technical data

Collector type	Type 15	Type 20	Type 25
Overall area [m²]	1.55	2.05	2.52
Absorber area [m²]	1.36	1.83	2.28
L x W x H [mm]	1531x1011x95	2031x1011x95	2031x1241x95
Absorber sheet	PVD Blue Selective Aluminum		
Absorption [%]	95		
Emission [%]	5		
Ø manifold [mm]	22		
Ø risers [mm]	8 or 15		
Connections Cu Ø 22	4 or 2		
Housing	Naval Aluminum		
Surface	Plain Aluminum		
Glass	3.2 mm tempered solar safety glass		
Transmittance of glass [%]	91 - 92		
Insulation	40 mm mineral wool plate		
Max. stagnation temperature	187 °C under test conditions		
Max. operating pressure	10 bar		
Proper heat transfer medium	Polypropylene glycol / water mixture		
Approved installation angle	min. 15°, max. 75°		
Packaging	Customised		
Position	Vertical or Horizontal		







11.000m² production facilities
500.000m² annual capacity
42 years of experience

2nd km Argos-Nafplio | 21200, Argos, Greece tel: +30 27510 20920-2 sales@dimas-solar.gr

sales@dimas-solar.gr www.dimas-solar.gr