



MULTI-SPINDLE MACHINING CENTER

JS-D1360-2

Technical Specification

Version 2025

**SHENZHEN JOJOY SEIKO CO., LTD.
HUIZHOU JOJOY SEIKO CO., LTD.**

General Description



Under the background of increasingly fierce competition in the modern manufacturing and machining industry, JOJOY SEIKO has creatively introduced the **Multi-spindle Machining Center Series** with **an innovative and unique structural design** to help our customers significantly **reduce costs** and **increase efficiency**. It can not only effectively control the costs of purchasing, labor and land etc., but also the efficiency is even **several times higher** than that of universal machining centers of the world's top brands.

Features

- + The main structure of machine tool is consisted of **only cast iron HT300** with high stability and rigidity.
- + **2-spindle design** means which can achieve **2-purpose simultaneous machining** to improve the efficiency heavily with relatively independent **2 spindles, 1 worktable and 2 servo ATCs**.
- + All the servo motors are equipped with absolute value bus encoders for accuracy compensation independently.
- + 4-axis or 5-axis rotary table and probe optional for customized requirements.

Technical Data

TECHNICAL DATA	UNITS	JS-D1360-2
Travel & Range		
X/Y Travel	mm	680/650
Z-axis Travel	mm	600*2
Distance from spindle nose to countertop	mm	150-800
Worktable		
Quantity	-	1
Worktable size	mm	1360*600
Max. loading capacity	kg	600
T-slot (width/quantity/distance)	mm/pcs/mm	18/5/100
Spindle		
Quantity	-	2
Distance between spindles	mm	680
Max. spindle speed	rpm	10000/12000
Spindle taper	-	BT 40
Spindle power	kw	7.5/11
Drive type	-	Direct-drive
Spindle cooling system	-	Oil cooling (Opt.)
Controller & Servo System		
CNC controller	-	SYNTEC
X/Y/Z servo motor power	kw	11/11
Z-axis servo motor power	kw	4.4*2
Servo ATC		
Quantity	-	2
Capacity	T	24T*2
Max. tool diameter	mm	80
Max. tool length	mm/kg	300
Tool-to-tool	s	6
Feed Rate		
X/Y/Z Rapid traverse	mm/min	36000
X/Y/Z Cutting speed	mm/min	10000
Accuracy		
X/Y/Z Positioning accuracy	mm	±0.005/300
X/Y/Z Repeatability	mm	±0.003/300
Other Data		
Air source required	Kgf/cm ²	6.5
Gross weight	kg	7500
Overall dimension (L*W*H)	mm	3160*2300*2950
Rated power	kw	20

Standard Accessories

ITEMS	BRAND	ORIGIN	REMARKS
CNC controller	SYNTEC	Taiwan	-
Spindle Inverter	SYNTEC	Taiwan	-
X/Y/Z servo motor	SYNTEC/INOVANCE	Taiwan/China	-
Spindle	DEJO/SPINDER	Taiwan	-
Ball screw	THK/IF	Japan/Germany	HIWIN/PMI Optional
Rolling guide	THK/REXROTH	Japan/Germany	X/Y/Z: 45/45/45mm
Bearing	NACHI/NSK	Japan	-
Coupling	NBK	Japan	-
Servo ATC	-	China	24T*2
Electrical components	SCHNEIDER	France	-
Pneumatic system	SMC	Japan	-
Lubricating system	BAOTN	China	-
Spindle cooling system	-	China	Oil cooling optional
Cutting coolant system	-	China	-
Tool setter	-	China	Contact measurement
AC for electrical cabinet	-	China	
Air though spindle	-	China	-
Electronic handwheel	-	China	-
Bottom chip flushing	-	China	2 Screw-type

Optional Accessories

NO.	OPTIONS
1	HNC / MITSUBISHI / FANUC CNC controller
2	Variable spindle power/speed/torque
3	4-axis / 5-axis rotary table
4	Probe for workpiece set-up & inspection
5	Chain-type chip conveyor
6	Oil cooler
7	Oil mist collector
8	Oil-water separator

Inspection and Acceptance

In case this is the part of the contract, the Seller shall notify the Buyer of the specified time for inspection at least 30 days in advance, and the Buyer shall send a representative to the Seller's factory, before packaging the equipment, to execute it in accordance with the requirements stipulated in the contract as following:

- **Standard 3-axis simultaneous cutting test and measurement.**
- **Positioning accuracy test and measurement.**
- **Other specific and reasonable tests and measurements.**

If the Buyer's representative fails to arrive at the Seller's factory for inspection as scheduled, the contractual equipment will not be delayed in packaging and delivery. Therefore, the Buyer's representative could only complete the procedure on other equipment of the same model or be regarded as a waiver of it.

The Seller shall provide the Buyer with the inspection report obtained according to the requirements stipulated in the contract, and if the inspection results meet the requirements, it shall be deemed that the contractual equipment has passed the inspection. The Buyer and the Seller shall then sign the acceptance confirmation.

Technical Documents

- **Operation Manual * 1 Copy**
- **Programming Manual * 1 Copy**
- **Mechanical Manual * 1 Copy**
- **Electrical Manual * 1 Copy**

Seal and Signature

■ **The Seller**

■ **The Buyer**