

TERRY H2O RO 375



INSTALLATION KIT
10, 16, OR 20 GALLON TANK AVAILABLE

Terry H2O RO 375 – Precision RO Filtration for Specialty Coffee and Food Service

Building on the foundation of the Terry H2O RO 250, the Terry H2O RO 375 elevates water filtration with increased capacity, improved efficiency, and uncompromising water quality—perfect for specialty coffee shops and demanding food service environments. Compact yet powerful, the Terry H2O RO 375 delivers exceptional performance in a space-saving format that's easy to install and service.

All three models share the same sleek stainless steel enclosure with tool-free service access via top and side panels, ensuring quick maintenance in high-traffic cafés and bars

- **TERRY H2O RO 375**: Utilizes standard incoming line pressure—ideal for locations with stable municipal supply.
- **TERRY H2O RO 375 (w/ Booster Pump)**: Integrates a booster pump kit with solenoid valve, booster pump, and tank pressure switch, designed to maintain optimal performance in low-pressure or fluctuating environments.
- **Terry H2O RO 650**: Utilizes two RO membranes to achieve 650 GPD of pure water, and one single remineralization + carbon post filter.

Key Features (All Terry H2O RO Models)

- Stainless steel enclosure with removable top and side panels for easy service access
- Three integrated pressure gauges (feed, pump, and tank) for real-time system monitoring
- Integrated TDS monitor for reading in and out water quality
- Bulkhead quick-connect fittings for clean and simple installation
- High-efficiency permeate pump reduces wastewater and improves membrane performance
- High-quality, USA-made filters designed for reliability and purity
- Manual membrane flush valve for startup and maintenance flushing

TERRY H2O SOLUTIONS
6641 W FRYE ROAD, CHANDLER, AZ 85226
800.852.4221
support@terryh2o.com

TERRY H2O RO COMPARISON CHART

TERRY H2O SOLUTIONS

MODEL NAME	Terry H2O RO 375	Terry H2O RO 375 (w/ Booster Pump)	Terry H2O RO 650
FLOW RATE	(x1) 325 GPD Membrane, 375 GPD w/ Blending	325 GPD Membrane, 375 GPD w/ Blending	(x2) 325 GPD Membrane, 650 GPD w/ Blending
RECOVERY %	40%	40%	30%
DIMENSIONS (IN.)	18.4 (H) x 9.4 (W) x 20.1 (D)	18.4 (H) x 9.4 (W) x 20.1 (D)	18.4 (H) x 9.4 (W) x 20.1 (D)
WEIGHT (LBS)	40	50	50
APPLICATION	Coffee/Food Service, Combi Ovens, Steam Ovens	Coffee/Food Service, Combi Ovens, Steam Ovens	Coffee/Food Service, Combi Ovens, Steam Ovens
FILTER STYLE	(5) Quick Twist Cartridges	(5) Quick Twist Cartridges	(5) Quick Twist Cartridges
CONNECTION	3/8 Quick-Connect (Feed, Tank, Pure), 1/4 Quick-Connect (Drain)	3/8 Quick-Connect (Feed, Tank, Pure), 1/4 Quick-Connect (Drain)	3/8 Quick-Connect (Feed, Tank, Pure), 1/4 Quick-Connect (Drain)
POWER	N/A	120v AC	120v AC