

PRODUCT FAMILY DATASHEETPARATHOM CLASSIC P DIM

Dimmable LED lamps, classic mini-ball shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Very long lifetime of up to 25,000 h
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

PRODUCT FEATURES

- LED alternative to conventional lamps
- Good quality of light; color rendering index R_a : \geq 80; constant chromaticity
- High color consistency: < 6 SDCM
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps



TECHNICAL DATA


	Electrical da	Electrical data				Photometrical data				
Product description	Nominal wattage	Nominal voltage	Max. lamp no. on circuit break. 10 A (B)	Max. lamp no. on circuit break. 16 A (B)	Nominal luminous	Rated luminous flux	Color temper-	Lumen main.fact.at end of nom.life time	Light color (designation)	
					flux		ature			
P CLAS P 40 FR 5.3 W/2700K E14 ¹⁾	5.30 W	220240 V	150	250	470 lm	470 lm	2700 K	0.70	Warm White	
P CLAS P 40 FR 5 W/2700K E14 ¹⁾	5.00 W	220240 V	150	250	470 lm	470 lm	2700 K	0.70	Warm White	
P CLAS P 40 FR 6 W/2700K E14 ¹⁾	6.00 W	220240 V			470 lm	470 lm	2700 K	0.70	Warm White	


				Light technical data	Dimensions & weight		Temperatures & operating conditions	Lifespan	
Product description	Color temper- ature	Luminous flux	Color render- ing index Ra	Warm-up time (60 %)	Overall length	Diameter	Maximum temperature at to test point	Nominal lamp life time	Number of switching cycles
P CLAS P 40 FR 5.3 W/2700K E14 ¹⁾	2700 K	470 lm	≥80	< 0.50 s	78.0 mm	45.0 mm	104 °C	25000 h	100000
P CLAS P 40 FR 5 W/2700K E14 ¹⁾	2700 K	470 lm	≥80	< 0.50 s	78.0 mm	45.0 mm	104 °C	25000 h	100000
P CLAS P 40 FR 6 W/2700K E14 ¹⁾	2700 K	470 lm	≥80	< 0.50 s	80.0 mm	45.0 mm	104 °C	25000 h	100000


	Additional product data			Capabilities	Certificates & standards		Country-specific categorizations
Product description	Base (standard designation)	Mercury content	Mercury- free	Dimmable	Energy efficiency class	Energy consumption	ILCOS
P CLAS P 40 FR 5.3 W/2700K E14 ¹⁾	E14	0.0 mg	Yes	Yes	A+	6 kWh/1000h	
P CLAS P 40 FR 5 W/2700K E14 ¹⁾	E14	0.0 mg	Yes	Yes	A+	6 kWh/1000h	
P CLAS P 40 FR 6 W/2700K E14 ¹⁾	E14	0.0 mg	Yes	Yes ²⁾	A+	6 kWh/1000h	DRBP/F-6,2-220-240-E14-43/89

¹⁾ All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In preparation

²⁾ With many common dimmers







P CLAS P 40 FR 5.3 W/2700K E14, P CLAS P 40 FR 5 W/2700K E14, P CLAS P 40 FR 6 W/2700K E14 P CLAS P 40 FR 5.3 W/2700K E14, P CLAS P 40 FR 5 W/2700K E14

P CLAS P 40 FR 6 W/2700K E14

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075147942	Shipping carton box 10	240 mm x 101 mm x 108 mm	518.00 g	2.62 dm ³
4058075292369	Shipping carton box 10	240 mm x 101 mm x 108 mm	518.00 g	2.62 dm ³
4052899962484	Shipping carton box 10	240 mm x 101 mm x 108 mm	568.00 g	2.62 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For dimming conformity see

www.ledvance.com/dim

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.