

Date

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (III/2)	400 V
Rated surge voltage (III/2)	4 kV
Rated current	18 A
Legend (ratings)	(III / 2) ≙ Overvoltage category III / Pollution degree 2

Approvals per UL 1059

Approvals per	UL 1059
---------------	---------

Connection data

Connection technology	PUSH WIRE®
Solid conductor	0,5 ... 1,5 mm <sup>2</sup> / 20 ... 16 AWG

Supus modificărilor.

Strip length	8 ... 9 mm / 0.31 ... 0.35 inch
Pole No.	2
Solid conductor 2	0,5 ... 2,5 mm <sup>2</sup> / 20 ... 14 AWG
Total number of connection points	8
Total number of potentials	2
Number of connection types	1

### Geometrical Data

Width	18,5 mm / 0.728 inch
Height	19 mm / 0.748 inch
Depth	24,5 mm / 0.965 inch

### Material Data


Fire load	0,107 MJ
Weight	6,2 g

### Commercial data


Product Group	8 (Misc. Chassis Mount Blocks)
Packaging type	bag
Country of origin	PL
GTIN	4044918397094
Customs tariff number	85369010000

### Aprobări / certificate

#### Country specific Approvals

Emblemă	Aprobare	Text de aprobare suplimentar	Nume certificat
	CSA DEKRA Certification B.V.	C22.2 No. 158	70048844

#### UL-Approvals

Emblemă	Aprobare	Text de aprobare suplimentar	Nume certificat
	UR Underwriters Laboratories Inc.	UL 1059	20190731- E45172

Supus modificărilor.



WAGO Kontakttechnik GmbH & Co. KG  
/Representative Office Romania  
Sos. Pipera-Tunari nr. 1/1  
building 1, 2nd floor | 077190 Voluntari, Ilfov  
Tel.: +40-(0)31 421 85 68 | Email: info-RO@wago.com

Aveți întrebări despre produsele noastre?  
Vă stăm la dispoziție pentru preluarea apelului la +40 (0) 31 421 85 68.

## Counterpart

## Produse compatibile


### assembling

	<b>Nr. articol: 271-702</b> Pins; for plate thickness 1 mm	<a href="http://www.wago.com/271-702">www.wago.com/271-702</a>
	<b>Nr. articol: 271-711</b> Pins; for plate thickness 1 mm	<a href="http://www.wago.com/271-711">www.wago.com/271-711</a>
	<b>Nr. articol: 271-712</b> Pins; for plate thickness 1.5 mm	<a href="http://www.wago.com/271-712">www.wago.com/271-712</a>

### ferrule

	<b>Nr. articol: 209-151</b> Pin terminals; insulated; suitable for 271 and 272 Series; green	<a href="http://www.wago.com/209-151">www.wago.com/209-151</a>
	<b>Nr. articol: 209-157</b> Pin terminals; insulated; suitable for 271 and 272 Series; blue	<a href="http://www.wago.com/209-157">www.wago.com/209-157</a>
	<b>Nr. articol: 209-164</b> Pin terminals; insulated; suitable for 271 and 272 Series; natural	<a href="http://www.wago.com/209-164">www.wago.com/209-164</a>

### tools

	<b>Nr. articol: 249-100</b> Operating tool; for terminal blocks with snap-in ground contact	<a href="http://www.wago.com/249-100">www.wago.com/249-100</a>
--	--	--

## Descărcări

### Documentation

#### Additional Information

Technical explanations

Apr 3, 2019

pdf  
3,6 MB

Descărcare

## Installation Notes

Supus modificărilor.