

## OTL95-3 grey 3xAl/Cu 6-95mm<sup>2</sup> 1000V Universal terminal

SKU	MAA3095A10
EAN	4744397014313
Color	Grey
Wire material	Al/Cu
Cross-section min. (mm <sup>2</sup> )	6
Cross-section max. (mm <sup>2</sup> )	95
Input wire min. (mm <sup>2</sup> )	6
Input wire max. (mm <sup>2</sup> )	95
Output wire min. (mm <sup>2</sup> )	6
Output wire max. (mm <sup>2</sup> )	95
Number of connections	6
Nominal current (A)	245 (Cu) / 220 (Al)
Nominal voltage (V)	1000
Service temperature (°C)	80
Material	Tin-plated aluminium, polyamide PA66
Mounting method	DIN rail, screw
Item width (mm)	59
Item length (mm)	84



<b>Item height (mm)</b>	51
<b>Item weight (g)</b>	178
<b>Screw</b>	Hex 6
<b>Tightening torque (Nm)</b>	12 Nm (6 - 25 mm <sup>2</sup> ) 22 Nm (35 - 95 mm <sup>2</sup> )
<b>IP rating</b>	IP20
<b>Certification</b>	EN 61238-1; EN60947-7-1; UL1059
<b>Flame resistance</b>	UL94 V0
<b>CN8 code</b>	85369010
<b>Package quantity (pcs)</b>	6