

## OJL400AF blue in 10x(1x25) out 4x35/3X50mm<sup>2</sup> Distribution block

<b>SKU</b>	MAB1403B10
<b>EAN</b>	4744397018922
<b>Color</b>	Blue
<b>Wire material</b>	Al/Cu
<b>Cross-section min. (mm<sup>2</sup>)</b>	2,5
<b>Cross-section max. (mm<sup>2</sup>)</b>	50
<b>Input wire min. (mm<sup>2</sup>)</b>	1 x 10x1x25 CU
<b>Input wire max. (mm<sup>2</sup>)</b>	1 x 10x1x25 CU
<b>Output wire min. (mm<sup>2</sup>)</b>	4 x 2,5 / 3 x 6
<b>Output wire max. (mm<sup>2</sup>)</b>	4 x 35 / 3 x 50
<b>Number of connections</b>	8
<b>Nominal current (A)</b>	425 (Cu) / 380 (Al)
<b>Nominal voltage (V)</b>	1000
<b>Service temperature (°C)</b>	80
<b>Material</b>	Tin-plated aluminium, polyamide PA66
<b>Mounting method</b>	DIN rail, screw
<b>Item width (mm)</b>	51,4
<b>Item length (mm)</b>	100,3



<b>Item height (mm)</b>	51,2
<b>Item weight (g)</b>	247
<b>Screw</b>	Hex 4 / 5
<b>Flexibar max. width (mm)</b>	25
<b>Flexibar max. layers</b>	10
<b>Tightening torque (Nm)</b>	6 Nm (2,5 - 35 mm <sup>2</sup> ) 10 Nm (6 - 50 mm <sup>2</sup> ) 10 Nm (10x Cu 1x25 mm <sup>2</sup> )
<b>IP rating</b>	IP20
<b>Certification</b>	EN 61238-1:2003; EN 60947-7-1:2019
<b>CN8 code</b>	85369010
<b>Package quantity (pcs)</b>	8