

OJL400ASF in 10x(1x25) out 4x35/3X50mm² Distribution block, sealing

SKU	MAB1404S10
EAN	4744397014498
Color	Grey
Wire material	Al/Cu
Cross-section min. (mm²)	2,5
Cross-section max. (mm²)	50
Input wire min. (mm²)	1 x 10x1x25 CU
Input wire max. (mm²)	1 x 10x1x25 CU
Output wire min. (mm²)	4 x 2,5 / 3 x 6
Output wire max. (mm²)	4 x 35 / 3 x 50
Number of connections	8
Nominal current (A)	425 (Cu) / 380 (Al)
Nominal voltage (V)	1000
Service temperature (°C)	80
Material	Tin-plated aluminium, polyamide PA66
Mounting method	DIN rail, screw
Item width (mm)	51,4
Item length (mm)	100,3



Item height (mm)	51,2
Item weight (g)	247
Screw	Hex 4 / 5
Flexibar max. width (mm)	25
Flexibar max. layers	10
Tightening torque (Nm)	6 Nm (2,5 - 35 mm ²) 10 Nm (6 - 50 mm ²) 10 Nm (10x Cu 1x25 mm ²)
IP rating	IP20
Certification	EN 61238-1:2003; EN 60947-7-1:2022
CN8 code	85369001
Package quantity (pcs)	8