

## SR95R 1xAl/Cu 16-95mm<sup>2</sup> 690V Device connector, right-handed

<b>SKU</b>	MAC9507A10
<b>EAN</b>	4744397018328
<b>Color</b>	Grey
<b>Wire material</b>	Al/Cu
<b>Cross-section min. (mm<sup>2</sup>)</b>	16
<b>Cross-section max. (mm<sup>2</sup>)</b>	95
<b>Input wire min. (mm<sup>2</sup>)</b>	16
<b>Input wire max. (mm<sup>2</sup>)</b>	95
<b>Number of connections</b>	1
<b>Nominal current (A)</b>	230 (Cu) / 180 (Al)
<b>Nominal voltage (V)</b>	690
<b>Service temperature (°C)</b>	80
<b>Material</b>	Tin-plated aluminium, polyamide PA66
<b>Mounting method</b>	Device
<b>Item width (mm)</b>	23,4
<b>Item length (mm)</b>	67,8
<b>Item height (mm)</b>	51
<b>Item weight (g)</b>	56



<b>Screw</b>	Hex 6
<b>Tightening torque (Nm)</b>	12 Nm (16 - 50 mm <sup>2</sup> ) 20 Nm (70 - 95 mm <sup>2</sup> )
<b>IP rating</b>	IP20
<b>Certification</b>	EN 61238-1:2003; EN 60947-7-1:2009
<b>CN8 code</b>	85369001
<b>Package quantity (pcs)</b>	30