

## SLT50-4 ye/gr Al 10-50/Cu 2.5-35 mm<sup>2</sup> 1000V Distribution block

<b>SKU</b>	MAS4050Y10
<b>Color</b>	Yellow/green
<b>Wire material</b>	Al/Cu
<b>Cross-section min. (mm<sup>2</sup>)</b>	2,5
<b>Cross-section max. (mm<sup>2</sup>)</b>	50
<b>Input wire min. (mm<sup>2</sup>)</b>	2,5
<b>Input wire max. (mm<sup>2</sup>)</b>	50
<b>Output wire min. (mm<sup>2</sup>)</b>	2,5
<b>Output wire max. (mm<sup>2</sup>)</b>	50
<b>Number of connections</b>	4
<b>Nominal current (A)</b>	135 / 145
<b>Nominal voltage (V)</b>	1000
<b>Material</b>	Tin-plated aluminium, polyamide PA66
<b>Item width (mm)</b>	60
<b>Item length (mm)</b>	29
<b>Item height (mm)</b>	17
<b>Item weight (g)</b>	41,8
<b>Screw</b>	Hex 5



<b>Tightening torque (Nm)</b>	3 Nm (2,5-16 mm <sup>2</sup> ) 8 Nm (25-50 mm <sup>2</sup> )
<b>IP rating</b>	IP23
<b>Certification</b>	EN 60947-7-1:2009, EN 61238-1:2003
<b>CN8 code</b>	85369010
<b>Package quantity (pcs)</b>	18