




ALMINO PD

quad, LED outdoor surface-mounted ceiling light,
UGR<19, grey IP65 4000K

With the ALMINO luminaire family we are providing ceiling lights and wall lights which can be optionally suspended for professional use with the highest demands. Thanks to the robust casing and the built-in LEDs, the luminaires provide efficient basic lighting with limited direct glare (UGR<19) and are therefore particularly suitable for industrial areas, warehouses and logistics areas. A suspension set and mounting brackets are available as optional accessories.



TECHNICAL DATA

Item no.:	1002194
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	1200 mA/V
Length	85.6 cm
Width	19.6 cm
Height	10.9 cm
Net weight	4.859 kg
Gross weight	6.129 kg
IP Code	IP 65
Safety class	II
Impact resistance class	IK08
Assembly	Surface
Assembly details	Ceiling with Acc.
Wattage	190 W
Lumen	24000 lm
Colour temperature	4000 Kelvin
Beam angle	50 °
Color	grey
CRI	>80
UGR ≤	19
Binning	3

LXXBXX data	70/10
Service life	50000 h
Minimum ambient temperature	-30 °C
Maximum ambient temperature	60 °C

Notes