### . . . . . . . . . . . . а. Л ы . . . . . . . . . . . **...** ..... . . . . . . . . . . . . . Ц л - **1** гг 1 . . . . . . . . . . . . . . . . . . . л







## L-LINE 120

# wall and ceiling light, T16, IP43, silver-grey, L/W/H 120/7/7 cm, max. 28W

The wall and ceiling light L-LINE 120 is made from silver-grey painted aluminium and equipped with a diffuser made from polycarbonate. The L-shaped basic design of the fitting provides glare-free illumination properties and can be used on surfaces such as mirrors. Designed for energy-saving T5 fluorescent tubes, the L-LINE wall and ceiling light is supplied ready for direct connection to 230V mains supply via the incorporated, electronic ballast.

## **TECHNICAL DATA**

| Item no.:               | 157424                 |
|-------------------------|------------------------|
| Socket                  | G5                     |
| Lamp                    | T16                    |
| Number of sockets       | 1                      |
| Lamps included          | 0                      |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Width                   | 120.0 cm               |
| Height                  | 7.0 cm                 |
| Depth                   | 7.0 cm                 |
| Net weight              | 2.386 kg               |
| Gross weight            | 2.76 kg                |
| IP Code                 | IP 43                  |
| Safety class            | 1                      |
| Assembly                | Surface                |
| Assembly details        | Wall                   |
| Wattage                 | 31.5 W                 |
| Color                   | grey                   |
|                         |                        |

### **Recommended lamp**

548028 T5 , fluorescent tube 28W, 3000K

Notes