





FLOOD LIGHT

outdoor façade light, LED, 5700K IP65, matt black, 100°, 36W

Powerful FLOOD LIGHT spot for illuminating areas and spaces. With a tiltable installation bracket and protection class IP65, the spot is suitable for outdoor installation on the wall, ceiling or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. An earth spike is available as an option for simplified floor installation.



TECHNICAL DATA

| | |
|-------------------------|-----------------------|
| Item no.: | 231161 |
| Lamps included | 0 |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Vertical tilting range | 180 ° |
| Length | 25.0 cm |
| Width | 9.0 cm |
| Height | 31.5 cm |
| Net weight | 2.886 kg |
| Gross weight | 3.185 kg |
| IP Code | IP 65 |
| Safety class | I |
| Impact resistance class | IK04 |
| Impact resistance | 0,5 Joule |
| Assembly | Surface |
| Assembly details | Ceiling, Ground, Wall |
| Wattage | 36 W |
| Lumen | 2400 lm |
| Colour temperature | 5700 Kelvin |
| Beam angle | 100 ° |
| Color | black |
| CRI | >70 |
| LXXBXX data | 70/50 |

| | |
|---------------------|---------|
| Service life | 30000 h |
| Ambient temperature | 40 °C |

Accessories

| | |
|--------|--|
| 234340 | Wall bracket , for Outdoor Beam and MI-LOX floodlight, black, 50cm |
| 234350 | WALL BRACKET , for SPOODI 15/20/31, black, 80 cm |
| 900011 | PLASTIC EARTH SPIKE , black, length 17.5cm |

Notes
