



## LED PANEL

**recessed and surface-mounted ceiling light, CL 136, anodised aluminium, 39.6W, 24V/DC, 3000K, 595x595mm**

With the LED PANEL, available in neutral or warm white colour, we offer a modern, space-saving solution for an efficient type of base lighting. Designed for ceiling grids with 60x60 cm size, the LED PANEL is supplied ready for installation. For grid ceilings 62 x 62 cm size, we offer a suitable adapter. The spacers supplied ensure simplified mounting to ceilings. With a total power of about 50W and a luminous flux of about 2500 lumens, you achieve more than just a pleasant, uniform and glare-free illumination. To operate the LED PANEL, the connection to a suitable LED power supply providing 24V DC is necessary.

## TECHNICAL DATA

<b>Item no.:</b>	158502
<b>Lamps included</b>	0
<b>Primary nominal voltage</b>	24V mA/V
<b>Length</b>	59.6 cm
<b>Width</b>	59.6 cm
<b>Height</b>	3.2 cm
<b>Net weight</b>	4.408 kg
<b>Gross weight</b>	5.103 kg
<b>IP Code</b>	IP 20
<b>Safety class</b>	III
<b>Assembly</b>	Recessed
<b>Assembly details</b>	Ceiling, Ceiling
<b>Color</b>	aluminium
<b>CRI</b>	>80
<b>Ambient temperature</b>	50 °C



## Accessories

158110	GRID CEILING LUMINAIRE ADAPTER , to fit in 62x62cm grid ceilings
--------	---

## Notes

---

---

---

---

---