



LED PANEL

recessed and surface-mounted ceiling light, CL 136, anodised aluminium, 39.6W, 24V/DC, 5500K, 595x595mm

With the LED PANEL, available in neutral or warm white colour, we offer a modern, space-saving solution for an efficient type of base lighting. Designed for ceiling grids with 60x60 cm size, the LED PANEL is supplied ready for installation. For grid ceilings 62 x 62 cm size, we offer a suitable adapter. The spacers supplied ensure simplified mounting to ceilings. With a total power of about 50W and a luminous flux of about 2500 lumens, you achieve more than just a pleasant, uniform and glare-free illumination. To operate the LED PANEL, the connection to a suitable LED power supply providing 24V DC is necessary.

TECHNICAL DATA

| | |
|-------------------------|------------------|
| Item no.: | 158501 |
| Lamps included | 0 |
| Primary nominal voltage | 24V mA/V |
| Length | 59.6 cm |
| Width | 59.6 cm |
| Height | 3.2 cm |
| Net weight | 4.587 kg |
| Gross weight | 5.156 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling, Ceiling |
| Color | aluminium |
| CRI | >80 |
| Ambient temperature | 50 °C |



Accessories

| | |
|--------|---|
| 158110 | GRID CEILING LUMINAIRE ADAPTER , to fit in 62x62cm grid ceilings |
|--------|---|

Notes
