

QUADRASYL D

Outdoor ceiling light, energy saving lamp GX53, IP23, square, silver-grey, max. 9W

The QUADRASYL D high-voltage recessed fitting is made from aluminium and is designed for the use of energy-saving GX53 lamps. A front cover made from stainless steel 316 completes the puristic and linear design. Rated IP23 QUADRASYL D can also be used in damp areas.

TECHNICAL DATA

| /FO |
|---------------|
| K 53 |
| R-TSE |
| |
| |
| 0V ~50Hz mA/V |
| .4 cm |
| .4 cm |
| 9 cm |
| 297 kg |
| 331 kg |
| 23 |
| |
| rface |
| iling,Wall |
| N |
| ЭУ |
| |

| | | | | | | | 4 | | | | 4 | | | 4 | | - | | 4 | 4 | 4 | 4 | ч | 4 | 4 | 4 | 4 | 4 | | | | | | | | | |
|---|----|-----|---|---|---|---|----|---|---|----|----|---|----|---|---|----|----|----|----|----|----|----|----|---|---|----|---|---|----|---|---|---|---|---|---|----|
| | J. | - 4 | | J | J | J | J. | J | J | a, | J | J | J | J | J | a, | a | a, | J. | | | | | | | | | | | | | | | | | |
| u | J | ר ר | J | J | 1 | J | J | J | J | ı | J. | J | J | J | J | J | J | | 4 | | | J | | 1 | | 4 | 4 | 1 | J. | 4 | ı | ı | ı | 1 | ı | J, |
| | | | | | ā | | | а | | a. | | а | a. | а | а | a. | a. | J. | J. | a. | a. | a. | J. | ı | ı | a. | а | а | | | | | | | | |



Recommended lamp

| 551372 | LED GX53 , SMD LED, 3W, 3000K, not dimmable |
|--------|---|
| | |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |